



---

NORDUGRID-MANUAL-13

26/7/2011

## ARC CLIENTS

*User Manual for client versions 1.0.0 and above*



# Contents

<b>1</b>	<b>Introduction</b>	<b>5</b>
<b>2</b>	<b>Commands</b>	<b>7</b>
2.1	Proxy utilities . . . . .	7
2.1.1	arcproxy . . . . .	7
2.1.2	arcslcs . . . . .	9
2.2	Job submission and management . . . . .	9
2.2.1	arcsub . . . . .	9
2.2.2	arcstat . . . . .	13
2.2.3	arccat . . . . .	14
2.2.4	arcget . . . . .	15
2.2.5	arcsync . . . . .	16
2.2.6	arcinfo . . . . .	17
2.2.7	arckill . . . . .	17
2.2.8	arcclean . . . . .	18
2.2.9	arc renew . . . . .	19
2.2.10	arc resume . . . . .	20
2.2.11	arc sub . . . . .	21
2.2.12	arc migrate . . . . .	22
2.3	Data manipulation . . . . .	23
2.3.1	arcls . . . . .	23
2.3.2	arccp . . . . .	24
2.3.3	arcrm . . . . .	25
2.3.4	arcs rmping . . . . .	26
2.3.5	chelonias . . . . .	26
2.4	Test suite . . . . .	33
<b>3</b>	<b>URLs</b>	<b>35</b>
<b>4</b>	<b>ARC Client Configuration</b>	<b>39</b>
4.1	Block [common] . . . . .	39
	defaultservices . . . . .	39
	rejectservices . . . . .	40
	verbosity . . . . .	40

timeout . . . . .	40
brokername . . . . .	40
brokerarguments . . . . .	40
joblist . . . . .	41
bartender . . . . .	41
proxypath . . . . .	41
keypath . . . . .	41
certificatepath . . . . .	41
cacertificatesdirectory . . . . .	41
cacertificatepath . . . . .	42
vomsserverpath . . . . .	42
username . . . . .	42
password . . . . .	42
keypassword . . . . .	42
keysize . . . . .	42
certificatelifetime . . . . .	42
slcs . . . . .	42
storedirectory . . . . .	43
jobdownloaddirectory . . . . .	43
idpname . . . . .	43
4.2 Block [alias] . . . . .	43
4.3 srms.conf . . . . .	43
4.4 Deprecated configuration files . . . . .	44

# Chapter 1

## Introduction

The command line user interface of ARC consists of a set of commands necessary for job submission and manipulation and data management. This manual replaces the older version in `NORDUGRID-MANUAL-1` and is valid for ARC versions 0.9 and above. Command line tools semantics is the same as in earlier versions of ARC, roughly following that of basic Linux commands and most common batch system commands. One obvious difference is change of the legacy prefix from “ng” to the more appropriate “arc”. This is not only a cosmetic change: **behaviour of the commands also have changed**, as did their functionalities and options.

Users are strongly discouraged from modifying their old scripts by simply replacing “ng” with “arc”  
– results may be unpredictable.



# Chapter 2

## Commands

### 2.1 Proxy utilities

ARC now comes complete with a set of utilities to create temporary user credentials (proxies) used to access Grid services.

#### 2.1.1 arcproxy

In order to contact Grid services (submit jobs, copy data, check information etc), one has to present valid credentials. These are commonly formalized as so-called “proxy” certificates. There are many different types of proxy certificates, with different Grids and different services having own preferences. **arcproxy** is a powerful tool that can be used to generate most commonly used proxies. It supports the following types:

- pre-RFC GSI proxy
- RFC-compliant proxy (default)
- VOMS-extended proxy
- MyProxy delegation

**arcproxy** requires presence of user’s private key and public certificate, as well as the public certificate of their issuer CA.

#### **arcproxy [options]**

Options:

-P, --proxy	<i>path</i>	path to the proxy file
-C, --cert	<i>path</i>	path to the certificate file
-K, --key	<i>path</i>	path to the key file
-T, --cadir	<i>path</i>	path to the trusted certificate directory, only needed for VOMS client functionality
-V, --vomses	<i>path</i>	path to the VOMS server configuration file
-S, --voms	<i>voms[:command]</i>	Specify VOMS server (more than one VOMS server can be specified like this: -voms VOa:command1 -voms VOb:command2) :command is optional, and is used to ask for specific attributes(e.g. roles). Command options are:

		all – put all of this DN's attributes into AC;
		list – list all of the DN's attribute, will not create AC extension;
		/Role=yourRole – specify the role, if this DN has such a role, the role will be put into AC
		/voname/groupname/Role=yourRole – specify the VO, group and role; if this DN has such a role, the role will be put into AC
-o, --order	<i>group[:role]</i>	Specify ordering of attributes, Examples: -order /knowarc.eu/coredev:Developer,/knowarc.eu/testers:Tester -order /knowarc.eu/coredev:Developer,/knowarc.eu/testers:Tester
-G, --gsicom		use GSI communication protocol for contacting VOMS services
-O, --old		use GSI proxy (default is RFC 3820 compliant proxy)
-I, --info		print all information about this proxy. In order to show the Identity (DN without CN as suffix for proxy) of the certificate, the 'trusted certdir' is needed.
-r, --remove		removes the proxy file
-U, --user	<i>string</i>	username for MyProxy server
-L, --myproxysrv	<i>URL</i>	URL of MyProxy server
-M, --myproxycmd	<i>PUT GET</i>	command to MyProxy server. The command can be PUT and GET.  PUT/put – put a delegated credential to MyProxy server;  GET/get – get a delegated credential from MyProxy server, credential (certificate and key) is not needed in this case.
-c, --constraint	<i>string</i>	proxy constraints
-t, --timeout	<i>seconds</i>	timeout in seconds (default 20 seconds)
-d, --debug	<i>debuglevel</i>	debug level is one of FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG
-z, --conffile	<i>filename</i>	configuration file (default \$HOME/.arc/client.conf)
-v, --version		print version information
-h, --help		print help page

Note that it does not make sense to specify the order of attributes if you have two or more different VOMS servers specified.

MyProxy functionality can be used together with VOMS functionality.

Supported constraints are:

- **validityStart=time** – e.g. 2008-05-29T10:20:30Z; time when certificate becomes valid. Default is now.
- **validityEnd=time** – time when certificate becomes invalid. Default is 43200 (12 hours) from start.
- **validityPeriod=time** – e.g. 43200 or 12h or 12H; for how long certificate is valid. If neither **validityPeriod** nor **validityEnd** are specified, default is 12 hours
- **vomsACvalidityPeriod=time** – e.g. 43200 or 12h or 12H; for how long the AC is valid. Default is the same as **validityPeriod**.



- `proxyPolicy=policy content` – assigns specified string to proxy policy to limit it's functionality.
- `proxyPolicyFile=policy file`

### 2.1.2 arcslcs

This utility generates short-lived credential based on the credential to IdP in SAML2SSO profile (normally the username/password to Shibboleth IdP).

#### arcslcs [options]

Options:

<code>-S, --ur;</code>	<i>URL</i>	URL of SLCS Service (e.g. <code>https://127.0.0.1:60000/slcs</code> )
<code>-I, --idp</code>	<i>URL</i>	the name of IdP (e.g. <code>https://idp.testshib.org/idp/shibboleth</code> )
<code>-U, --user</code>	<i>string</i>	User account to IdP
<code>-P, --password</code>	<i>string</i>	password for user account to IdP
<code>-Z, --keysize</code>	<i>integer</i>	size of the private key, default is 1024
<code>-K, --keypass</code>		passphrase for protecting the private key; if not set, the private key file will not be protected by the passphrase.
<code>-L, --lifetime</code>	<i>hours</i>	life time of the credential (hours), starting with current time
<code>-D, --storedir</code>	<i>path</i>	store directory of the credential
<code>-d, --debug</code>	<i>debuglevel</i>	debug level is one of FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG
<code>-z, --conffile</code>	<i>filename</i>	configuration file (default <code>\$HOME/.arc/client.conf</code> )
<code>-v, --version</code>		print version information
<code>-h, --help</code>		print help page

## 2.2 Job submission and management

The following commands are used for job submission and management, such as status check, results retrieval, cancellation, re-submission and such. The jobs must be described using a job description language. ARC supports the following languages: JSDL [2], xRSL [9] and JDL [7].

### 2.2.1 arcsub

The `arcsub` command is the most essential one, as it is used for submitting jobs to the Grid resources. `arcsub` matches user's job description to the information collected from the Grid, and the optimal site is being selected for job submission. The job description is then being forwarded to that site, in order to be submitted to the Local Resource Management System (LRMS), which can be, e.g., PBS or Condor or SGE etc.

#### arcsub [options] [filename ...]

Options:

<code>-c, --cluster</code>	<code>[-] url</code>	explicitly select or reject (-) a specific site
<code>-g, --index</code>	<code>[-] url</code>	explicitly select or reject (-) a specific index server
<code>-e, --jobdescrstring</code>	<i>filename</i>	string describing the job to be submitted
<code>-f, --jobdescrfile</code>	<i>filename</i>	file describing the job to be submitted
<code>-j, --joblist</code>	<i>filename</i>	the file storing information about active jobs (default <code>\$/arc/jobs.xml</code> )
<code>-o, --jobids-to-file</code>	<i>filename</i>	the IDs of the submitted jobs will be appended to this file
<code>-D, --dryrun</code>		add dryrun option to the job description
<code>-x, --dumpdescription</code>		do not submit – dump transformed job description to stdout
<code>-b, --broker</code>	<i>string</i>	select broker method (default is Random)
<code>-t, --timeout</code>	<i>seconds</i>	timeout in seconds (default 20)
<code>-d, --debug</code>	<i>debuglevel</i>	debug level, FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG - default WARNING
<code>-z, --conffile</code>	<i>filename</i>	configuration file (default <code>\$HOME/.arc/client.conf</code> )
<code>-v, --version</code>		print version information
<code>-h, --help</code>		print help page

Arguments:

*filename* ...                      file(s) describing the job(s) to be submitted

The `-c` and `-g` arguments accept meta-URLs of the format `GRID:URL`, where `GRID:` is optional, and it specifies the Grid middleware plugin to be used handle the given URL. Possible options are:

**ARC0** Legacy ARC execution service (requires the `nordugrid-arc-plugins-globus` package to be installed)

**ARC1** Webservice ARC execution service

**CREAM** CREAM execution service

**BES** Generic BES plugin complying to the OGSA-BES standard

For example, for index servers:

`index.ng.org/mds-vo-name=sweden`

`cream.glite.org`

or being more specific:

`ARC0:ldap://index.ng.org:2135/mds-vo-name=sweden,o=grid`

`CREAM:ldap://cream.glite.org:2170/o=grid`

or clusters:

`ce.ng.eu`

or with all details:

`ARC0:ldap://ce.ng.eu:2135/nordugrid-cluster-name=ce.ng.eu,Mds-Vo-name=local,o=grid`

There are some defaults for these URLs, e.g. in the ARC0 and CREAM case, you may only specify the hostname, the rest of the URL will be automatically generated, in the ARC1 case https protocol is assumed. If the `GRID` part of the meta-URL is not specified, all of the available Grid middleware plugins will be tried. It is recommended to use aliases for these URLs. Aliases are specified in the configuration file (see Section 4).

As a shorthand `-f` can be omitted if the job description file is put last on the commandline.

A simple "Hello World" job can look like:

```
arcsb -c my-test-site job.jsdl
```

The `-c` option can be repeated several times, for example:

```
arcsb -c alias1 -c alias2 job.xrsl
```

This will submit a job to either `alias1` or `alias2`. To submit a job to any site except `badsite`, use `-sign` in front of the name:

```
arcsb -c -badsite job.xrsl
```

If option `-c` is not given, the `arcsb` command locates the available sites by querying the Information System. Default index services for the Information System are specified in the configuration template distributed with the middleware, and can be overwritten both in the user's configuration (see Section 4) and from the command line using option `-g`. Different Grids use different notation for such index services.

A user has to have valid credentials (see Section 2.1) and be authorised at the specified site. A test file `job.jsdl` is shown below.

```
<?xml version="1.0" encoding="UTF-8"?>
<JobDefinition
  xmlns="http://schemas.ggf.org/jsdl/2005/11/jsdl"
  xmlns:posix="http://schemas.ggf.org/jsdl/2005/11/jsdl-posix">
  <JobDescription>
    <JobIdentification>
      <JobName>Hello World job</JobName>
    </JobIdentification>
    <Application>
      <posix:POSIXApplication>
        <posix:Executable>/bin/echo</posix:Executable>
        <posix:Argument>'Hello World'</posix:Argument>
        <posix:Output>out.txt</posix:Output>
        <posix:Error>err.txt</posix:Error>
      </posix:POSIXApplication>
    </Application>
  </JobDescription>
</JobDefinition>
```

If a job is successfully submitted, a **job identifier** (*job ID*) is printed to standard output.

The job ID uniquely identifies the job while it is being executed. Job IDs differ strongly between Grid middlewares, but basically they have a form of a URL. You should use Job ID as a handle to refer to the job when doing other job manipulations, such as querying job status (`arcstat`), killing it (`arckill`), re-submitting (`arcresub`), or retrieving the result (`arcget`).

Usually job ID is a valid URL for the job session directory. You can always use it to access the files related to the job, by using data management tools (see Chapter 2.3).

There may be exception for some computational services like CREAM which do not support listing job session directory.

For advanced computational jobs which may need to communicate their presence to some service outside there may be need for knowing own job ID. For jobs accepted by ARC computational services this information may be found in local (for job executable) environment variable `GRID_GLOBAL_JOBID`. One need to take into account that this ID may be different from one provided by `arcsb`. Example is ID provided by A-REX computational service. That service provides OGSA BES compatible interface for job management and ID contains XML document according to OGSA BES specifications.

The job description in one of the supported languages can be given, either as an argument on the command line, or can be read from a file. Several jobs can be requested at the same time by giving more than one filename argument, or by repeating the `-f` or `-e` options. It is possible to mix `-e` and `-f` options in the same `arcsub` command.

In order to keep track of submitted jobs, ARC client stores information in a dedicated file, by default located in `$HOME/.arc/jobs.xml`. It is sometimes convenient to keep separate lists (e.g., for different kinds of jobs), to be used later with e.g. `arcstat`. This is achieved with the help of `-j` command line option.

The user interface transforms input job description into a format that can be understood by the Grid services to which it is being submitted. By specifying the `--dumpdescription` option, such transformed description is written to stdout instead of being submitted to the remote site.

Possible broker values for the `arcsub` command line option `-b` are:

- **Random** – ranks targets randomly (default)
- **FastestQueue** – ranks targets according to their queue length
- **Benchmark[:name]** – ranks targets according to a given benchmark, as specified by the **name**. If no benchmark is specified, CINT2000 \* is used
- **Data** – ranks targets according the amount of megabytes of the requested input files that are already in the computing resources cache.
- **Python:<module>.<class>[:arguments]** – ranks targets using any user-supplied custom Python broker module, optionally with broker arguments. Such module can reside anywhere in user's `PYTHONPATH`
- **<otherbroker>[:arguments]** – ranks targets using any user-supplied custom C++ broker plugin, optionally with broker arguments. Default location for broker plugins is `/usr/lib/arc` (may depend on the operating system), or the one specified by the `ARC_PLUGIN_PATH`.

To write a custom broker in C++ one has to write a new specialization of the **Broker** base class and implement the **SortTargets** method in the new class. The class should be compiled as a loadable module that has the proper ARC plugin descriptor for the new broker. For example, to build a broker plugin “MyBroker” one executes:

```
g++ -I /arc-install/include \
    -L /arc-install/lib \
    `pkg-config --cflags glibmm-2.4 libxml-2.0` \
    -o libaccmybroker.so -shared MyBroker.cpp
```

For more details, refer to *libarclib* documentation [4].

It often happens that some sites that `arcsub` has to contact are slow to answer, or are down altogether. This will not prevent you from submitting a job, but will slow down the submission. To speed it up, you may want to specify a shorter timeout (default is 20 seconds) with the `-t` option:

```
arcsub -t 5 myjob.jsdl
```

Default value for the timeout can be set in the user's configuration file.

If you would like to get diagnostics of the process of resource discovery and requirements matching, a very useful option is `-d`. The following command:

```
arcsub -d VERBOSE myjob.xrsl
```

will print out the steps taken by the ARC client to find the best cluster satisfying your job requirements. Possible diagnostics degrees, in the order of increasing verbosity, are: **FATAL**, **ERROR**, **WARNING**, **INFO**,

---

\*<http://www.spec.org/cpu2000/CINT2000/>

VERBOSE and DEBUG. Default is WARNING, and it can be set to another value in the user's configuration file.

Default configuration file is `$HOME/.arc/client.conf`. However, a user can choose any other pre-defined configuration through option `-z`.

Command line option `-v` prints out version of the installed ARC client, and option `-h` provides a short help text.

### 2.2.2 arcstat

#### arcstat [options] [job ...]

Options:

<code>-a, --all</code>		all jobs
<code>-j, --joblist</code>	<i>filename</i>	the file storing information about active jobs (default <code>\$HOME/.arc/jobs.xml</code> )
<code>-i, --jobids-from-file</code>	<i>filename</i>	file containing a list of jobIDs
<code>-c, --cluster</code>	<code>[-] name</code>	explicitly select or reject a specific site
<code>-s, --status</code>	<i>statusstr</i>	only select jobs whose status is <i>statusstr</i>
<code>-l, --long</code>		long format (extended information)
<code>-S, --sort</code>	<i>criterion</i>	sort jobs according to jobid, submissiontime or job-name
<code>-R, --rsort</code>	<i>criterion</i>	reverse sorting of jobs according to jobid, submissiontime or jobname
<code>-p, --print-jobids</code>		instead of the status only the IDs of the selected jobs will be printed
<code>-t, --timeout</code>	<i>time</i>	timeout for queries (default 20 sec)
<code>-d, --debug</code>	<i>debuglevel</i>	debug level is one of FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG
<code>-z, --conffile</code>	<i>filename</i>	configuration file (default <code>\$HOME/.arc/client.conf</code> )
<code>-v, --version</code>		print version information
<code>-h, --help</code>		print help page

Arguments:

`job ...` list of job IDs and/or jobnames

The `arcstat` command returns the status of jobs in the Grid, and is typically issued with a job ID (as returned by `arcsub`) as an argument. It is also possible to use job name instead of ID, but if several jobs have identical names, information will be collected about all of them. More than one job ID and/or name can be given.

When several of the `-c <cluster>`, `-i <jobidfile>` and `[job...]` command line options are specified, the command returns information about all jobs listed on the command line plus all jobs on the specified clusters plus all jobs from the specified jobidfiles.

However the `-c <cluster>` and `-s <status>` options will filter the jobs selected by the above mentioned options, or if none of those are specified, then these will filter all the jobs.

For example, `arcstat -s Finished -c mycluster <jobid>` will return information about the finished jobs on mycluster plus about <jobid> but only if it is finished. Or, `arcstat -i jobidfile -c -mycluster` will return information about jobs which are in the jobidfile but not on mycluster.

If the `-l` option is given, extended information is printed.

Jobs can be sorted according to the `jobid`, `submissiontime` or `jobname`, either in normal or reverse order. By using the `--sort` or `--rsort` option followed by the desired ordering (`jobid`, `submissiontime` or `jobname`), jobs will be sorted in normal or reverse order. Note that the options `--sort` and `--rsort` cannot be used at the same time.

Options `-a`, `-c`, `-s` and `-j` do not use job ID or names. By specifying the `-a` option, the status of all active jobs will be shown. If the `-j` option is used, the list of jobs is read from a file with the specified filename, instead of the default one (`$HOME/.arc/jobs.xml`).

Option `-c` accepts arguments in the `GRID:URL` notation, as explained in the description of `arcsub`, or their aliases as specified in the configuration file.

Different sites may report different job states, depending on the installed grid middleware version. Typical values can be e.g. “Accepted”, “Preparing”, “Running”, “Finished” or “Deleted”. Please refer to the respective middleware documentation for job state model description.

Command line option `-s` will instruct the client to display information of only those jobs which status matches the instruction. This option must be given together with either `-a` or `-c` ones, e.g.:

```
arcstat -as Finished
```

Other command line options are identical to those of `arcsub`.

### 2.2.3 arccat

It is often useful to monitor the job progress by checking what it prints on the standard output or error. The command `arccat` assists here, extracting the corresponding information from the execution cluster and dumping it on the user’s screen. It works both for running tasks and for the finished ones. This allows a user to check the output of the finished task without actually retrieving it.

**arccat [options] [job ...]**

Options:

<code>-a, --all</code>		all jobs
<code>-j, --joblist</code>	<i>filename</i>	the file storing information about active jobs (default <code>/.arc/jobs.xml</code> )
<code>-i, --jobids-from-file</code>	<i>filename</i>	file containing a list of jobIDs
<code>-c, --cluster</code>	<code>[-] url</code>	explicitly select or reject (-) a specific site
<code>-s, --status</code>	<i>statusstr</i>	only select jobs whose status is <i>statusstr</i>
<code>-o, --stdout</code>		show the stdout of the job (default)
<code>-e, --stderr</code>		show the stderr of the job
<code>-l, --joblog</code>		show the CE’s error log of the job
<code>-t, --timeout</code>	<i>time</i>	timeout for queries (default 20 sec)
<code>-d, --debug</code>	<i>debuglevel</i>	debug level is one of FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG
<code>-z, --conf file</code>	<i>filename</i>	configuration file (default <code>\$HOME/.arc/client.conf</code> )
<code>-v, --version</code>		print version information
<code>-h, --help</code>		print help page

Arguments:

<code>job ...</code>	list of job IDs and/or jobnames
----------------------	---------------------------------

The **arccat** command returns the standard output of a job (**-o** option), the standard error (**-e** option) or errors reported by either Grid Manager or A-REX (**-l** option).

Other command line options have the same meaning as in **arcstat**.

When several of the **-c <cluster>**, **-i <jobidfile>** and **[job...]** command line options are specified, the command prints logs of all jobs listed on the command line plus all jobs on the specified clusters plus all jobs from the specified jobidfiles.

However the **-c -<cluster>** and **-s <status>** options will filter the jobs selected by the above mentioned options, or if none of those are specified, then these will filter all the jobs.

For example, **arccat -s Finished -c mycluster <jobid>** will print logs of the finished jobs on mycluster plus of <jobid> but only if it is finished. Or, **arccat -i jobidfile -c -mycluster** will print logs of jobs which are in the jobidfile but not on mycluster.

## 2.2.4 arcget

To retrieve the results of a finished job, the **arcget** command should be used. It will transfer the files specified for download in job description to the user's computer.

### arcget [options] [job ...]

Options:

<b>-a, --all</b>		all jobs
<b>-j, --joblist</b>	<i>filename</i>	the file storing information about active jobs (default <code>/.arc/jobs.xml</code> )
<b>-i, --jobids-from-file</b>	<i>filename</i>	file containing a list of jobIDs
<b>-c, --cluster</b>	<b>[-]</b> <i>name</i>	explicitly select or reject a specific site (cluster)
<b>-s, --status</b>	<i>statusstr</i>	only select jobs whose status is <i>statusstr</i>
<b>-D, --dir</b>	<i>dirname</i>	download path (the job directory will be created in that location)
<b>-J, --usejobname</b>	<i>dirname</i>	use the jobname instead of the short ID as the job directory name
<b>-k, --keep</b>		keep files in the Grid (do not clean)
<b>-f, --force</b>		force download (overwrite existing job directory)
<b>-t, --timeout</b>	<i>time</i>	timeout for queries (default 20 sec)
<b>-d, --debug</b>	<i>debuglevel</i>	debug level is one of FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG
<b>-z, --conffile</b>	<i>filename</i>	configuration file (default <code>\$HOME/.arc/client.conf</code> )
<b>-v, --version</b>		print version information
<b>-h, --help</b>		print help page

Arguments:

**job ...** list of job IDs and/or jobnames

Only the results of jobs that have finished can be downloaded. Just like in **arcstat** and **arccat** cases, the job can be referred to either by the **jobID** that was returned by **arcsub** at submission time, or by its name, if the job description contained a job name attribute.

By default, the job is downloaded into a newly created directory in the current path, with the name typically being a large random number. In order to instruct **arcget** to use another path, use option **-D**

(note the capital “D”), e.g.

```
arcget -D /tmp/myjobs "Test job nr 1"
```

After downloading, your jobs will be erased from the execution site! Use command line option `-k` to keep finished jobs in the Grid.

Other command line options are identical to those of e.g. `arcstat`.

When several of the `-c <cluster>`, `-i <jobidfile>` and `[job...]` command line options are specified, the command retrieves all jobs listed on the command line plus all jobs on the specified clusters plus all jobs from the specified jobidfiles.

However the `-c <cluster>` and `-s <status>` options will filter the jobs selected by the above mentioned options, or if none of those are specified, then these will filter all the jobs.

For example, `arcget -s Finished -c mycluster <jobid>` will retrieve the finished jobs on `mycluster` plus `<jobid>` but only if it is finished. Or, `arcget -i jobidfile -c -mycluster` will retrieve jobs which are in the `jobidfile` but not on `mycluster`.

### 2.2.5 arcsync

It is advised to start every grid session by running `arcsync`, especially when changing workstations. The reason is that your job submission history is cached on your machine, and if you are using ARC client installations on different machines, your local lists of submitted jobs will be different. To synchronise these lists with the information in the Information System, use the `arcsync` command.

#### arcsync [options]

Options:

<code>-c, --cluster</code>	<code>[-]name</code>	explicitly select or reject a specific site
<code>-g, --index</code>	<code>url</code>	explicitly select or reject (-) a specific index server
<code>-j, --joblist</code>	<code>filename</code>	the file storing information about active jobs (default <code>/.arc/jobs.xml</code> )
<code>-f, --force</code>		don't ask for confirmation
<code>-T, --truncate</code>		truncate the job list before synchronising
<code>-t, --timeout</code>	<code>seconds</code>	timeout in seconds (default 20)
<code>-d, --debug</code>	<code>debuglevel</code>	debug level, FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG - default WARNING
<code>-z, --conffile</code>	<code>filename</code>	configuration file (default <code>\$HOME/.arc/client.conf</code> )
<code>-v, --version</code>		print version information
<code>-h, --help</code>		print help page

The ARC client keeps a local list of jobs in the user's home directory. If this file is lost, corrupt, or the user wants to recreate the file on a different workstation, the `arcsync` command will recreate this file from the information available in the Information System.

Since the information about a job retrieved from a cluster can be slightly out of date if the user very recently submitted or removed a job, a warning is issued when this command is run. The `-f` option disables this warning.



If the job list is not empty when invoking synchronisation, the old jobs will be merged with the new jobs, unless the `-T` option is given (note the capital “T”), in which case the job list will first be truncated and then the new jobs will be added.

### 2.2.6 arcinfo

The `arcinfo` command is used to obtain status information about clusters on the Grid.

#### arcinfo [options]

Options:

<code>-c, --cluster</code>	<code>[-]name</code>	explicitly select or reject a specific site
<code>-g, --index</code>	<code>url</code>	explicitly select or reject (-) a specific index server
<code>-l, --long</code>		long format (extended information)
<code>-t, --timeout</code>	<code>seconds</code>	timeout in seconds (default 20)
<code>-d, --debug</code>	<code>debuglevel</code>	debug level, FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG - default WARNING
<code>-z, --conffile</code>	<code>filename</code>	configuration file (default <code>\$HOME/.arc/client.conf</code> )
<code>-v, --version</code>		print version information
<code>-h, --help</code>		print help page

The `arcinfo` command is used to obtain information about clusters and queues (*targets*) available on the Grid. Either the `--cluster` or `--index` flag should be used to specify the target(s) which should be queried for information. Both of these flags take a service endpoint as argument. See `arcsub` and the configuration notes in Section 4 for description of these.

Detailed information about queried computing services can be obtained by specifying the `--long` flag.

When specifying the `--index` flag, the information about the computing services registered at the index server will be queried, rather than the status of the index server itself.

### 2.2.7 arckill

It happens that a user may wish to cancel a job. This is done by using the `arckill` command. A job can be killed almost at any stage of processing through the Grid.

#### arckill [options] [job ...]

Options:

<code>-a, --all</code>		all jobs
<code>-j, --joblist</code>	<code>filename</code>	the file storing information about active jobs (default <code>/.arc/jobs.xml</code> )
<code>-i, --jobids-from-file</code>	<code>filename</code>	file containing a list of jobIDs
<code>-c, --cluster</code>	<code>[-]url</code>	explicitly select or reject (-) a specific site
<code>-s, --status</code>	<code>statusstr</code>	only select jobs whose status is <i>statusstr</i>
<code>-k, --keep</code>		keep files in the Grid (do not clean)
<code>-t, --timeout</code>	<code>time</code>	timeout for queries (default 20 sec)

<code>-d, --debug</code>	<i>debuglevel</i>	debug level is one of FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG
<code>-z, --conffile</code>	<i>filename</i>	configuration file (default \$HOME/.arc/client.conf)
<code>-v, --version</code>		print version information
<code>-h, --help</code>		print help page
Arguments:		
<code>job ...</code>		list of job IDs and/or jobnames

If a job is killed, its traces are being cleaned from the Grid. If you wish to keep the killed job in the system, e.g. for a post-mortem analysis, use the `-k` option.

Job cancellation is an asynchronous process, such that it may take a few minutes before the job is actually cancelled.

Command line options have the same meaning as the corresponding ones of `arcstat` and others.

When several of the `-c <cluster>`, `-i <jobidfile>` and `[job...]` command line options are specified, the command kills all jobs listed on the command line plus all jobs on the specified clusters plus all jobs from the specified jobidfiles.

However the `-c <cluster>` and `-s <status>` options will filter the jobs selected by the above mentioned options, or if none of those are specified, then these will filter all the jobs.

For example, `arckill -s INLRMS:R -c mycluster <jobid>` will kill the running jobs on `mycluster` plus `<jobid>` but only if it is running. Or, `arckill -i jobidfile -c -mycluster` will kill all jobs which are in the `jobidfile` but not on `mycluster`.

### 2.2.8 arcclean

If a job fails or gets killed with `-k` option, or when you are not willing to retrieve the results for some reasons, a good practice for users is not to wait for the system to clean up the job leftovers, but to use `arcclean` to release the disk space and to remove the job ID from the list of submitted jobs and from the Information System.

**arcclean [options] [job ...]**

Options:

<code>-a, --all</code>		all jobs
<code>-j, --joblist</code>	<i>filename</i>	the file storing information about active jobs (default <code>/.arc/jobs.xml</code> )
<code>-i, --jobids-from-file</code>	<i>filename</i>	file containing a list of jobIDs
<code>-c, --cluster</code>	<code>[-] name</code>	explicitly select or reject a specific site (cluster)
<code>-s, --status</code>	<i>statusstr</i>	only select jobs whose status is <i>statusstr</i>
<code>-f, --force</code>		removes the job ID from the local list even if the job is not found on the Grid
<code>-t, --timeout</code>	<i>time</i>	timeout for queries (default 20 sec)
<code>-d, --debug</code>	<i>debuglevel</i>	debug level is one of FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG
<code>-z, --conffile</code>	<i>filename</i>	configuration file (default \$HOME/.arc/client.conf)

<code>-v, --version</code>	print version information
<code>-h, --help</code>	print help page
Arguments:	
<code>job ...</code>	list of job IDs and/or jobnames

Only jobs that have finished or were cancelled can be cleaned.

It happens ever so often that the job is cleaned by the system, or is otherwise unreachable, and yet your local job list file still has it listed. Use `-f` option in this case to forcefully remove such stale job information from the local list.

Other command line options have the same meaning as the corresponding ones of `arcstat` and others.

When several of the `-c <cluster>`, `-i <jobidfile>` and `[job...]` command line options are specified, the command cleans all jobs listed on the command line plus all jobs on the specified clusters plus all jobs from the specified jobidfiles.

However the `-c <cluster>` and `-s <status>` options will filter the jobs selected by the above mentioned options, or if none of those are specified, then these will filter all the jobs.

For example, `arcclean -s FAILED -c mycluster <jobid>` will clean the failed jobs on `mycluster` plus `<jobid>` but only if it is failed. Or, `arcclean -i jobidfile -c -mycluster` will clean all jobs which are in the `jobidfile` but not on `mycluster`.

### 2.2.9 arc renew

Quite often, the user proxy expires while the job is still running (or waiting in a queue). In case such job has to upload output files to a Grid location (Storage Element), it will fail. By using the `arc renew` command, users can upload a new proxy to the job. This can be done while a job is still running, thus preventing it from failing.

If a job has failed in file upload due to expired proxy, `arc renew` can be issued within 24 hours (or whatever is the expiration time set by the site) after the job end, which must be followed by `arc resume`. The Grid Manager or A-REX will then attempt to finalize the job by uploading the output files to the desired location.

#### **arc renew [options] [job ...]**

Options:	
<code>-a, --all</code>	all jobs
<code>-j, --joblist</code>	<i>filename</i> the file storing information about active jobs (default <code>/.arc/jobs.xml</code> )
<code>-i, --jobids-from-file</code>	<i>filename</i> file containing a list of jobIDs
<code>-c, --cluster</code>	<code>[-] name</code> explicitly select or reject a specific site (cluster)
<code>-s, --status</code>	<i>statusstr</i> only select jobs whose status is <i>statusstr</i>
<code>-t, --timeout</code>	<i>time</i> timeout for queries (default 20 sec)
<code>-d, --debug</code>	<i>debuglevel</i> debug level is one of FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG
<code>-z, --conffile</code>	<i>filename</i> configuration file (default <code>\$HOME/.arc/client.conf</code> )
<code>-v, --version</code>	print version information
<code>-h, --help</code>	print help page
Arguments:	
<code>job ...</code>	list of job IDs and/or jobnames

Prior to using **arcnew**, be sure to actually create the new proxy by running **arcproxy**!

Command line options have the same meaning as the corresponding ones of **arcstat** and others.

When several of the **-c <cluster>**, **-i <jobidfile>** and **[job...]** command line options are specified, the command renews proxies of all jobs listed on the command line plus all jobs on the specified clusters plus all jobs from the specified jobidfiles.

However the **-c -<cluster>** and **-s <status>** options will filter the jobs selected by the above mentioned options, or if none of those are specified, then these will filter all the jobs.

For example, **arcnew -s FAILED -c mycluster <jobid>** will renew proxies of the failed jobs on **mycluster** plus **<jobid>** but only if it is failed. Or, **arcnew -i jobidfile -c -mycluster** will renew proxies of all jobs which are in the **jobidfile** but not on **mycluster**.

### 2.2.10 arcresume

In some cases a user may want to restart a failed job, for example, when input files become available, or the storage element for the output files came back online, or when a proxy is renewed with **arcnew**. This can be done using the **arcresume** command.

Make sure your proxy is still valid, or when uncertain, run **arcproxy** followed by **arcnew** before **arcresume**. The job will be resumed from the state where it has failed.

#### **arcresume [options] [job ...]**

<b>-a, --all</b>		all jobs
<b>-j, --joblist</b>	<i>filename</i>	the file storing information about active jobs (default <code>/.arc/jobs.xml</code> )
<b>-i, --jobids-from-file</b>	<i>filename</i>	file containing a list of jobIDs
<b>-c, --cluster</b>	<b>[-]name</b>	explicitly select or reject a specific site (cluster)
<b>-s, --status</b>	<i>statusstr</i>	only select jobs whose status is <i>statusstr</i>
<b>-t, --timeout</b>	<i>time</i>	timeout for queries (default 20 sec)
<b>-d, --debug</b>	<i>debuglevel</i>	debug level is one of FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG
<b>-z, --conffile</b>	<i>filename</i>	configuration file (default <code>\$HOME/.arc/client.conf</code> )
<b>-v, --version</b>		print version information
<b>-h, --help</b>		print help page
Arguments:		
<b>job ...</b>		list of job IDs and/or jobnames

Command line options have the same meaning as the corresponding ones of **arcstat** and others.

When several of the **-c <cluster>**, **-i <jobidfile>** and **[job...]** command line options are specified, the command resumes all jobs listed on the command line plus all jobs on the specified clusters plus all jobs from the specified jobidfiles.

However the `-c <cluster>` and `-s <status>` options will filter the jobs selected by the above mentioned options, or if none of those are specified, then these will filter all the jobs.

For example, `arcresume -s FAILED -c mycluster <jobid>` will resume the failed jobs on `mycluster` plus `<jobid>` but only if it is failed. Or, `arcresume -i jobidfile -c -mycluster` will resume all jobs which are in the `jobidfile` but not on `mycluster`.

### 2.2.11 arcresub

Quite often it happens that a user would like to re-submit a job, but has difficulties recovering the original job description xRSL file. This happens when xRSL files are created by scripts on-fly, and matching of xRSL to the job ID is not straightforward. The utility called `arcresub` helps in such situations, allowing users to resubmit jobs.

#### arcresub [options] [job ...]

Options:

<code>-a, --all</code>		all jobs
<code>-g, --index</code>	<i>url</i>	explicitly select or reject (-) a specific index server
<code>-j, --joblist</code>	<i>filename</i>	the file storing information about active jobs (default <code>/.arc/jobs.xml</code> )
<code>-i, --jobids-from-file</code>	<i>filename</i>	file containing a list of jobIDs
<code>-o, --jobids-to-file</code>	<i>filename</i>	the IDs of the submitted jobs will be appended to this file
<code>-c, --cluster</code>	<code>[-]name</code>	explicitly select or reject a specific source site
<code>-q, --qluster</code>	<code>[-]name</code>	explicitly select or reject a specific site as re-submission target
<code>-m, --same</code>		re-submit to the same site
<code>-s, --status</code>	<i>statusstr</i>	only select jobs whose status is <i>statusstr</i>
<code>-x, --dumpdescription</code>		do not submit – dump transformed job description to stdout
<code>-k, --keep</code>		keep files in the Grid (do not clean)
<code>-b, --broker</code>	<i>string</i>	select broker method (default is Random)
<code>-t, --timeout</code>	<i>time</i>	timeout for queries (default 20 sec)
<code>-d, --debug</code>	<i>debuglevel</i>	debug level is one of FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG
<code>-z, --conffile</code>	<i>filename</i>	configuration file (default <code>\$HOME/.arc/client.conf</code> )
<code>-v, --version</code>		print version information
<code>-h, --help</code>		print help page

Arguments:

<code>job ...</code>	list of job IDs and/or jobnames
----------------------	---------------------------------

More than one jobid and/or jobname can be given. If several jobs were submitted with the same jobname all those jobs will be resubmitted.

Upon resubmission of a job the corresponding job description will be fetched from the local job list file. If input files have changed since the original job submission, the job no longer remains the same job and will therefore not be resubmitted. To make sure the job is always resubmittable, submit it with `arcsub -n`.

In case the job description is not found in the joblist, an attempt will be made to retrieve it from the cluster holding the original job. This however may fail, since both the submission client and the cluster can have made modifications to the job description.

Upon resubmission the job will receive a new job ID. The old job ID will be kept in the local job list file, enabling future back tracing of the resubmitted job.

Regarding command line options, **arcresub** behaves much like **arcsub**, except that **-c** in this case indicates not the submission target site, but on the contrary, the **site from which the jobs will be resubmitted**. Submission target site is specified with option **-q**. If you wish to re-submit each job to the same site, use option **-m**.

If the original job was successfully killed, its traces will be removed from the execution site, unless the **-k** option is specified.

When several of the **-c <cluster>**, **-i <jobidfile>** and **[job...]** command line options are specified, the command resubmits all jobs listed on the command line plus all jobs on the specified clusters plus all jobs from the specified jobidfiles.

However the **-c <cluster>** and **-s <status>** options will filter the jobs selected by the above mentioned options, or if none of those are specified, then these will filter all the jobs.

For example, **arcresub -s FAILED -c mycluster <jobid>** will resubmit the running jobs on **mycluster** plus **<jobid>** but only if it is failed. Or, **arcresub -i jobidfile -c -mycluster** will resubmit all jobs which are in the **jobidfile** but not on **mycluster**.

### 2.2.12 arc migrate

Quite often jobs end up stuck in long queues, and users wish to migrate them to a better resource. Command **arc migrate** is triggering this migration. It applies only to jobs submitted to A-REX, as other Grid execution services do not support this functionality.

#### arc migrate [options] [job ...]

Options:

<b>-a, --all</b>		all jobs
<b>-g, --index</b>	<i>url</i>	explicitly select or reject (-) a specific index server
<b>-j, --joblist</b>	<i>filename</i>	the file storing information about active jobs (default <code>/.arc/jobs.xml</code> )
<b>-i, --jobids-from-file</b>	<i>filename</i>	file containing a list of jobIDs
<b>-o, --jobids-to-file</b>	<i>filename</i>	the IDs of the submitted jobs will be appended to this file
<b>-c, --cluster</b>	<b>[-] name</b>	explicitly select or reject a specific site (cluster)
<b>-q, --qluster</b>	<b>[-] name</b>	explicitly select or reject a specific site as re-submission target
<b>-f, --forcemigration</b>		force migration, ignoring kill failure
<b>-b, --broker</b>	<i>string</i>	select broker method (default is Random)
<b>-t, --timeout</b>	<i>time</i>	timeout for queries (default 20 sec)
<b>-d, --debug</b>	<i>debuglevel</i>	debug level is one of FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG
<b>-z, --conffile</b>	<i>filename</i>	configuration file (default <code>\$HOME/.arc/client.conf</code> )
<b>-v, --version</b>		print version information
<b>-h, --help</b>		print help page

Arguments:

`job ...` list of job IDs and/or jobnames

Currently only jobs having the A-REX status “Running”, “Executing” or “Queuing” can be migrated

Command line options `-c` and `#-q#` are interpreted in the same way as in `arcresub`, namely, `-c` indicates “from” and `#-q#` “to” which site the job will be migrated.

If the job(s) is successfully migrated, a new job ID(s) is printed out. This jobID uniquely identifies the job while it is being executed.

When several of the `-c <cluster>`, `-i <jobidfile>` and `[job...]` command line options are specified, the command migrates all jobs listed on the command line plus all jobs on the specified clusters plus all jobs from the specified jobidfiles.

However the `-c <cluster>` and `-s <status>` options will filter the jobs selected by the above mentioned options, or if none of those are specified, then these will filter all the jobs.

For example, `arcmigrate -s FAILED -c mycluster <jobid>` will migrate the running jobs on `mycluster` plus `<jobid>` but only if it is failed. Or, `arcmigrate -i jobidfile -c -mycluster` will resubmit all jobs which are in the `jobidfile` but not on `mycluster`.

## 2.3 Data manipulation

ARC provides basic data management tools, which are simple commands for file copy and removal, with eventual use of data indexing services.

### 2.3.1 arcls

`arcls` is a simple utility that allows to list contents and view some attributes of objects of a specified (by a URL) remote directory.

**`arcls [options] <URL>`**

Options:

<code>-l, --long</code>		detailed listing
<code>-L, --locations</code>		detailed listing including URLs from which files can be downloaded
<code>-m, --metadata</code>		display all available metadata
<code>-r, --recursive</code>	<i>recursion_level</i>	operate recursively (if possible) up to specified level (0 - no recursion)
<code>-n, --nolist</code>		show only description of requested object, do not list content of directories (like <code>ls -d</code> ).
<code>-c, --checkaccess</code>		check readability of object. Retrieving and showing information about object is suppressed.
<code>-t, --timeout</code>	<i>seconds</i>	timeout in seconds (default 20)
<code>-d, --debug</code>	<i>debuglevel</i>	debug level, FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG - default WARNING
<code>-z, --conffile</code>	<i>filename</i>	configuration file (default <code>\$HOME/.arc/client.conf</code> )

<code>-v, --version</code>	print version information
<code>-h, --help</code>	print help page
Arguments:	
URL	file or directory URL

This tool is very convenient not only because it allows to list files at a Storage Element or records in an indexing service, but also because it can give a quick overview of a job's working directory, which is explicitly given by job ID.

Usage examples can be as follows:

```
arcls -L rls://rls.nordugrid.org:38203/logical_file_name
arcls -l gsiftp://lscf.nbi.dk:2811/jobs/1323842831451666535
arcls srm://grid.uio.no:8446/srm/managerv2?SFN=/johndoe/log2
```

Examples of URLs accepted by this tool can be found in Section 3, though `arcls` won't be able to list a directory at an HTTP server, as they normally do not return directory listings.

### 2.3.2 arccp

`arccp` is a powerful tool to copy files over the Grid. It is a part of the A-REX, but can be used by the User Interface as well.

**arccp [options] <source> <destination>**

Options:

<code>-p, --passive</code>		use passive transfer (does not work if secure is on, default if secure is not requested)
<code>-n, --nopassive</code>		do not try to force passive transfer
<code>-f, --force</code>		if the destination is an indexing service and not the same as the source and the destination is already registered, then the copy is normally not done. However, if this option is specified the source is assumed to be a replica of the destination created in an uncontrolled way and the copy is done like in case of replication. Using this option also skips validation of completed transfers.
<code>-i, --indicate</code>		show progress indicator. If the transfer time is short then there may be no indicator.
<code>-T, --nottransfer</code>		do not transfer file, just register it - destination must be non-existing meta-url
<code>-u, --secure</code>		use secure transfer (insecure by default)
<code>-y, --cache</code>	<i>path</i>	path to local cache (use to put file into cache). See [6] for information on caching.
<code>-r, --recursive</code>	<i>recursion_level</i>	operate recursively (if possible) up to specified level (0 - no recursion)
<code>-R, --retries</code>	<i>number</i>	how many times to retry transfer of every file before failing
<code>-L, --location</code>	<i>URL</i>	physical file to write to when destination is an indexing service. Must be specified for indexing services which do not automatically generate physical locations. Can be specified multiple times - locations will be tried in order until one succeeds.



<b>-t, --timeout</b>	<i>seconds</i>	timeout in seconds (default 20)
<b>-d, --debug</b>	<i>debuglevel</i>	debug level, FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG - default WARNING
<b>-z, --conffile</b>	<i>filename</i>	configuration file (default \$HOME/.arc/client.conf)
<b>-v, --version</b>		print version information
<b>-h, --help</b>		print help page

Arguments:

<b>source</b>	source URL
<b>destination</b>	destination URL

This command transfers contents of a file between 2 end-points. End-points are represented by URLs or meta-URLs. For supported endpoints please refer to Section 3.

**arccp** can perform multi-stream transfers if **threads** URL option is specified and server supports it.

Source can end with **"/**. In that case, the set of files under source will be copied into destination and destination must also end with **"/**. Destination will be created if it does not exist. If copying deeper than one level is required then **-r** must be used. If destination alone ends with **"/**, it is extended with the part of source after last **"/**, thus allowing users to skip the destination file or directory name if it is meant to be identical to the source.

Usage examples of **arccp** are:

```
arccp gsiftp://lscf.nbi.dk:2811/jobs/1323842831451666535/job.out \
      file:///home/myname/job2.out
arccp gsiftp://aftpexp.bnl.gov;threads=10/rep/my.file \
      rls://grid.uio.no/zebra4.f
arccp http://www.nordugrid.org/data/somefile gsiftp://hathi.hep.lu.se/data/
arccp gsiftp://pgs02.grid.upjs.sk:2811/jobs/13331297786445657047863/ output/
arccp -L srm://srm.host.org/my.file.1 my.file lfc://lfc.host.org/grid/my.file
```

### 2.3.3 arcrm

The **arcrm** command allows users to erase files at any location specified by a valid URL.

**arcrm [options] <source>**

Options:

<b>-f, --force</b>		remove logical file name registration even if not all physical instances were removed
<b>-t, --timeout</b>	<i>seconds</i>	timeout in seconds (default 20)
<b>-d, --debug</b>	<i>debuglevel</i>	debug level, FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG - default WARNING
<b>-z, --conffile</b>	<i>filename</i>	configuration file (default \$HOME/.arc/client.conf)
<b>-v, --version</b>		print version information
<b>-h, --help</b>		print help page

Arguments:

<b>source</b>	source URL
---------------	------------

A convenient use for **arcrm** is to erase the files in a data indexing catalog (LFC, RLS or such), as it will not only remove the physical instance, but also will clean up the database record.

Here is an `arcrm` example:

```
arcrm lfc://grid.uio.no/grid/atlas/AOD_0947.pool.root
```

### 2.3.4 arcsrmping

The `arcsrmping` command is used to quickly test availability of an SRM service, similarly to the `ping` tool in Unix.

**arcsrmping [options] <service>**

Options:

<code>-t, --timeout</code>	<i>seconds</i>	timeout in seconds (default 20)
<code>-d, --debug</code>	<i>debuglevel</i>	debug level, FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG - default WARNING
<code>-z, --conffile</code>	<i>filename</i>	configuration file (default \$HOME/.arc/client.conf)
<code>-v, --version</code>		print version information
<code>-h, --help</code>		print help page

Arguments:

<i>service</i>	A URL to an SRM service
----------------	-------------------------

The `arcsrmping` command is a *ping* client for the SRM service. It sends an SRM ping request to the SRM service and displays the result.

### 2.3.5 chelonia

`chelonia` is a client tool for accessing the Chelonia storage system. With it it is possible to create, remove and list file collections, upload, download and remove files, and move and stat collections and files, using Logical Names (LN).

**chelonia [options] <method> [arguments]**

(ARC 0.9)

Options:

<code>-b</code>	<i>URL</i>	URL of Bartender to connect
<code>-x</code>		print SOAP XML messages
<code>-v</code>		verbose mode
<code>-z</code>	<i>filename</i>	configuration file (default \$HOME/.arc/client.conf)
<code>-w</code>		allow to run without the ARC python client libraries (with limited functionality)

Methods:

<code>stat</code>	<i>LN [LN ...]</i>	get detailed information about an entry or several
<code>makeCollection, make, mkdir</code>	<i>LN</i>	create a collection
<code>unmakeCollection, unmake, rmdir</code>	<i>LN</i>	remove an empty collection
<code>list, ls</code>	<i>LN</i>	list the content of a collection
<code>move, mv</code>	<i>source target</i>	move entries within the namespace (both LNs)
<code>putFile, put</code>	<i>source target</i>	upload a file from a <i>source</i> to a <i>target</i> (both specified as LNs)

<code>getFile, get</code>	<i>source [target]</i>	download a file from a <i>source</i> to a <i>target</i>
<code>delFile, del, rm</code>	<i>LN [LN ...]</i>	remove file(s)
<code>modify, mod</code>	<i>string</i>	modify metadata
<code>policy, pol</code>	<i>string</i>	modify access policy rules
<code>unlink</code>	<i>string</i>	remove a link to an entry from a collection without removing the entry itself
<code>credentialsDelegation, cre</code>	<i>string</i>	delegate credentials for using gateway
<code>removeCredentials, rem</code>	<i>string</i>	remove previously delegated credentials
<code>makeMountPoint, makemount</code>	<i>string</i>	create a mount point

Without arguments, each method prints its own help. Detailed explanation of each method is given below.

Examples:

```
chelonia list /
chelonia put orange /
chelonia stat /orange
chelonia get /orange /tmp
chelonia mkdir /fruits
chelonia mkdir /fruits/apple
chelonia mv /orange /fruits
chelonia ls /fruits
chelonia rmdir /fruits/apple
chelonia rmdir /fruits
chelonia rm /fruits/orange
chelonia policy / change ALL +read +addEntry
chelonia modify /pennys-orange set states neededReplicas 2
```

### stat

With the `stat` method it is possible to get all the metadata about one or more entry (file, collection, etc.). The entries are specified with their Logical Name (LN).

**chelonia stat <LN> [<LN> ...]**

The output contains key-value pairs grouped in sections. The ‘states’ section contains the size and the checksum of a file, the number of needed replicas, and whether a collection is closed or not; the ‘entry’ section contains the DN of the owner, the globally unique ID (GUID) of the entry, and the type of the entry (file, collection, etc.); the ‘parents’ section contains the GUID of the parent collection(s) of this entry, and the name of this entry in that collection separated with a ‘/’; the ‘locations’ sections contains the location of the replicas of a file, which contains of the ID (the URL) of the storage element, the ID of the replica within the storage element, and the state of the replica; the ‘timestamps’ section contains the creation time of the entry; the ‘entries’ section contains the name and GUID of the entries of a collection. Example stat of a file:

```
$ chelonia stat /thing
'/thing': found
states
  checksumType: md5
  neededReplicas: 3
  size: 6
  checksum: a0186a90393bd4a639a1ce35d8ef85f6
entry
  owner: /C=HU/O=NIIF CA/OU=GRID/OU=NIIF/CN=Nagy Zsombor
  GUID: 398CBDEA-E282-4735-8DF6-2464CD00BE2D
  type: file
```

```

parents
  0/thing: parent
locations
  https://localhost:60000/Shepherd D519F687-EF65-4AEA-9766-E6E2D42166C4: alive
timestamps
  created: 1257351119.3

```

Example stat of a collection:

```

$ chelonia stat /
'/' : found
states
  closed: no
entry
  owner: /C=HU/O=NIIF CA/OU=GRID/OU=NIIF/CN=Nagy Zsombor
  GUID: 0
  type: collection
timestamps
  created: 1257351114.37
entries
  thing: 398CBDEA-E282-4735-8DF6-2464CD00BE2D

```

### makeCollection

With the `makeCollection` or `mkdir` method it is possible to create a new empty collection. The requested Logical Name (LN) should be specified.

```
chelonia makeCollection <LN>
```

The parent collection of the requested Logical Name must exist.

Example output of the method:

```

$ chelonia mkdir /newcoll
Creating collection '/newcoll': done

$ chelonia mkdir /nonexistent/newcoll
Creating collection '/nonexistent/newcoll': parent does not exist

```

### unmakeCollection

With the `unmakeCollection` or `rmdir` method it is possible to delete an empty collection which is specified by its Logical Name (LN).

```
chelonia unmakeCollection <LN>
```

Example output of the method:

```

$ chelonia rmdir /newcoll
Removing collection '/newcoll': removed

$ chelonia rmdir /dir
Removing collection '/dir': collection is not empty

```

### list

With the `list` or `ls` method it is possible to list the contents of one or more collections which are specified by their Logical Name (LN).

```
chelonia list <LN> [<LN> ...]
```

Example output of the method:

```
$ chelonia list / /newcoll
'/newcoll': collection
  empty.
'/': collection
  thing    <file>
  dir      <collection>
  newcoll  <collection>
```

### **move**

With the `move` or `mv` method it is possible to move a file or collection within the namespace of `chelonia` (including renaming the entry). The source path and the target path should be specified as Logical Names

```
chelonia move <sourceLN> <targetLN>
```

Example output of the method:

```
$ chelonia mv /thing /newcoll/
Moving '/thing' to '/newcoll/': moved

$ chelonia mv /newcoll/thing /newcoll/othername
Moving '/newcoll/thing' to '/newcoll/othername': moved
```

### **putFile**

With the `putFile` or `put` method it is possible to upload a new file into the system creating a new Logical Name (LN). It is possible to specify the number of needed replicas.

```
chelonia putFile <source filename> <target LN> [<number of replicas needed>]
```

Example output of the method:

```
$ chelonia put thing /newcoll/
'thing' (6 bytes) uploaded as '/newcoll/thing'.
```

### **getFile**

With the `getFile` or `get` method it is possible to download a file specified with its Logical Name (LN). If the target local path is not given, then the file will be put into the local directory.

```
chelonia getFile <source LN> [<target filename>]
```

Example output of the method:

```
$ chelonia get /newcoll/thing newlocalname
'/newcoll/thing' (6 bytes) downloaded as 'newlocalname'.
```

### **delFile**

With the `delFile` or `rm` method it is possible to delete one or more files from the system.

```
chelonia delFile <LN> [<LN> ...]
```

Example output of the method:

```
$ chelonia rm /newcoll/othername
/newcoll/othername: deleted
```

## modify

With the `modify` or `mod` method it is possible to modify some metadata of an entry.

```
chelonia modify <LN> <changeType> <section> <property> <value>
```

The possible values of ‘changeType’ are ‘set’ (sets the property to value within the given section), ‘unset’ (removes the property from the given section - the ‘value’ does not matter) and ‘add’ (sets the property to value within the given section only if it does not exist yet).

To change the number of needed replicas for a file:

```
chelonia modify <LN> set states neededReplicas <number of needed replicas>
```

To close a collection:

```
chelonia modify <LN> set states closed yes
```

To change metadata key-value pairs:

```
chelonia modify <LN> set|unset|add metadata <key> <value>
```

## policy

With the `policy` or `pol` method it is possible to modify the policy of the entry

```
chelonia policy <LN> <changeType> <identity> <action list>
```

The possible values of ‘changeType’ are ‘set’ (sets the action list to the given user overwriting the old one), ‘change’ (modify the current action list with adding and removing actions) and ‘clear’ (clear the action list of the given user).

The ‘identity’ could be currently three things: the DN of a user; the name of a VO (with the syntax: ‘VOMS:<VO name>’); or ‘ALL’ for all users.

The ‘action list’ is a list of actions prefixed with ‘+’ or ‘-’, e.g. ‘+read +addEntry -delete’.

These are the actions which can be used for access control:

- *read*: user can get the list of entries in the collection; user can download the file
- *addEntry*: user can add a new entry to the collection;
- *removeEntry*: user can remove any entry from the collection
- *delete*: user can delete the collection if it is empty; user can delete a file
- *modifyPolicy*: user can modify the policy of the file/collection
- *modifyStates*: user can modify some special metadata of the file/collection (close the collection, change the number of needed replica of the file)
- *modifyMetadata*: user can modify the arbitrary metadata section of the file/collection (these are property-value pairs)

There is an implicit default policy: the owner always has all the rights. Checking the 'stat' of new collections:

```
$ chelonia stat /newcoll
'/newcoll': found
  states
    closed: no
  entry
    owner: /C=HU/O=NIIF CA/OU=GRID/OU=NIIF/CN=Nagy Zsombor
    GUID: 41CBD461-09BE-46FD-8A1B-767C7D427AF9
    type: collection
  parents
    0/newcoll: parent
  timestamps
    created: 1257435820.26
  entries
    thing: A63658B4-2C6E-46A3-8238-7D291F8F81C2
```

shows no policies, but it shows the owner. This collection has no additional policies just the default one: the owner can do anything, noone else can do anything.

Let's set it in a way that all users can read the contents of this collection:

```
$ chelonia policy /newcoll change ALL +read
Setting action list of '/newcoll' for user ALL to +read: set.
$ chelonia stat /newcoll
'/newcoll': found
  [...]
  policy
    ALL: +read
  [...]
```

Then we can set that all the members of the knowarc VO would be able to add entries to this collection:

```
$ chelonia policy /newcoll change VOMS:knowarc +addEntry
Setting action list of '/newcoll' for user VOMS:knowarc to +addEntry: set.
$ chelonia stat /newcoll
'/newcoll': found
  [...]
  policy
    ALL: +read
    VOMS:knowarc: +addEntry
  [...]
```

And for example we can set a specific user to be able to remove entries from this collections:

```
$ chelonia policy /newcoll change \
  "/C=HU/O=NIIF CA/OU=GRID/OU=NIIF/CN=TestUser" +removeEntry
Setting action list of '/newcoll'
  for user /C=HU/O=NIIF CA/OU=GRID/OU=NIIF/CN=TestUser to +removeEntry: set.
$ chelonia stat /newcoll'/newcoll': found
  [...]
  policy
    /C=HU/O=NIIF CA/OU=GRID/OU=NIIF/CN=TestUser: +removeEntry
    ALL: +read
    VOMS:knowarc: +addEntry
  [...]
```

## unlink

With the **unlink** method it is possible to remove a file or collection just from its parent collection without removing the file or collection itself.

**chelonia unlink <LN>**

If there is a file called ‘/newcoll/thing’, it is in the listing of the ‘/newcoll’ collection:

```
$ chelonia list /newcoll
'/newcoll': collection
  thing <file>
```

The file is in the entries of the collection:

```
$ chelonia stat /newcoll
'/newcoll': found
  entries
    thing: A63658B4-2C6E-46A3-8238-7D291F8F81C2
  [...]
```

It is possible the ‘stat’ the file with the Logical Name ‘/newcoll/thing’:

```
jim:~ zsombor$ chelonia stat /newcoll/thing
'/newcoll/thing': found
  states
    checksumType: md5
    neededReplicas: 3
    size: 6
    checksum: a0186a90393bd4a639a1ce35d8ef85f6
  [...]
```

Now with the ‘unlink’ method it is possible to remove the file from the ‘/newcoll’ collection, but not from the system:

```
$ chelonia unlink /newcoll/thing
Unlinking '/newcoll/thing': unset
```

Now the file is not in the collection anymore:

```
$ chelonia list /newcoll
'/newcoll': collection
  empty.
$ chelonia stat /newcoll/thing
'/newcoll/thing': not found
```

But with the GUID of the file, it can still be accessed:

```
$ chelonia stat A63658B4-2C6E-46A3-8238-7D291F8F81C2
'A63658B4-2C6E-46A3-8238-7D291F8F81C2': found
  states
    checksumType: md5
    neededReplicas: 3
    size: 6
    checksum: a0186a90393bd4a639a1ce35d8ef85f6
  [...]
```

**credentialDelegation**

With the `credentialDelegation` or `cre` method it is possible to delegate credentials to the Bartender.



**chelonia credentialDelegation****removeCredentials**

With the `removeCredentials` or `rem` method it is possible to remove the previously delegated credentials.

**chelonia removeCredentials****makeMountPoint**

With the `makeMountPoint` or `makemount` method it is possible to create a mount point within the namespace of Chelonia which points to a GridFTP server.

**chelonia makeMountPoint <LN> <URL>**

The ‘LN’ is the requested Logical Name for the mount point, the ‘URL’ points to the GridFTP server.

**unmakeMountPoint**

With the `unmakeMountPoint` or `unmount` method it is possible to remove a previously created mount point.

**chelonia unmakeMountPoint <LN>**

The ‘LN’ is the Logical Name of the mount point.

## 2.4 Test suite

The `arctest` utility is designed to run a suite of simple pre-defined test tasks, primarily in order to verify installation of clients and services. It also prints information about installed certificates .

**arctest [options]**

Options:

<code>-c, --cluster</code>	<code>[-] url</code>	explicitly select or reject (-) a specific site
<code>-g, --index</code>	<code>[-] url</code>	explicitly select or reject (-) a specific index server
<code>-J, --job</code>	<i>integer</i>	submit test job given by the number
<code>-j, --joblist</code>	<i>filename</i>	the file storing information about active jobs (default <code>\$/arc/jobs.xml</code> )
<code>-o, --jobids-to-file</code>	<i>filename</i>	the IDs of the submitted jobs will be appended to this file
<code>-D, --dryrun</code>		add dryrun option to the job description
<code>-x, --dumpdescription</code>		do not submit – dump transformed job description to stdout
<code>-E, --certificate</code>	<i>filename</i>	string describing the job to be submitted
<code>-b, --broker</code>	<i>string</i>	select broker method (default is Random)
<code>-t, --timeout</code>	<i>seconds</i>	timeout in seconds (default 20)

<code>-d, --debug</code>	<i>debuglevel</i>	debug level, FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG - default WARNING
<code>-z, --conffile</code>	<i>filename</i>	configuration file (default \$HOME/.arc/client.conf)
<code>-v, --version</code>		print version information
<code>-h, --help</code>		print help page
Arguments:		
<code>filename ...</code>		file(s) describing the job(s) to be submitted

Pre-defined test jobs are Grid-flavor specific and are used depending of the selected cluster.

The test jobs available in the current version of **arctest** are:

- This test job calculates prime numbers for 2 minutes and saves the list. The source code for the prime number program, the Makefile and the executable is downloaded to the cluster chosen from various servers and the program is compiled before the run. In this way, the test job constitutes a fairly comprehensive test of the basic setup of a Grid cluster.
- This test job does nothing but printing "hello, grid" to stdout.
- This test job tests download capabilities of the chosen cluster by downloading 8 input files over different protocols – HTTP, FTP, gsiFTP and RLS.

## Chapter 3

# URLs

File locations in ARC can be specified both as local file names, and as Internet standard *Uniform Resource Locators (URL)*. There are also some additional URL *options* that can be used.

The following transfer protocols and metadata servers are supported:

<b>ftp</b>	ordinary <i>File Transfer Protocol (FTP)</i>
<b>gsiftp</b>	GridFTP, the Globus <sup>®</sup> -enhanced FTP protocol with security, encryption, etc. developed by The Globus Alliance [5]
<b>http</b>	ordinary <i>Hyper-Text Transfer Protocol (HTTP)</i> with PUT and GET methods using multiple streams
<b>https</b>	HTTP with SSL v3
<b>httpg</b>	HTTP with Globus <sup>®</sup> GSI
<b>ldap</b>	ordinary <i>Lightweight Data Access Protocol (LDAP)</i> [10]
<b>rls</b>	Globus <sup>®</sup> <i>Replica Location Service (RLS)</i> [3]
<b>lfc</b>	LFC catalog and indexing service of EGEE gLite [1]
<b>srn</b>	Storage Resource Manager (SRM) service [8]
<b>arc</b>	for the Chelonia storage service, communicates with Bartenders, the path should be a Logical Name (LN) (supported only in <b>arcls</b> , <b>arcsb</b> and other <b>arc*</b> tools.)
<b>file</b>	local to the host file name with a full path

An URL can be used in a standard form, i.e.

```
protocol://[host[:port]]/file
```

Or, to enhance the performance, it can have additional options:

```
protocol://[host[:port]][:option[:option[...]]]/file
```

For a metadata service URL, construction is the following:

```
protocol://[url[|url[...]]@]host[:port][:option[:option[...]]/  
lfn[:metadataoption[:metadataoption[...]]]
```

In user-level tools, URLs may be expressed in this syntax, or there may simpler ways to construct complex URLs. In particular, command line tools such as **arccp** and the xRSL and JSDL job description languages provide methods to express URLs in a simpler way.

For Chelonia, the syntax is

```
arc://<LogicalName>[?BartenderURL=<URL>]
```

where the `BartenderURL` may come from the `bartender` parameter of the client configuration file. Note that Chelonia URLs are **not** supported in `ngls`, `ngsub` and other `ng*` tools.

For the SRM service, the syntax is

```
srn://host[:port][;options]/[service_path?SFN=]file
```

Versions 1.1 and 2.2 of the SRM protocol are supported. The default `service_path` is `srn/managerv2` when the server supports v2.2, `srn/managerv1` otherwise.

The URL components are:

<code>host[:port]</code>	Hostname or IP address [and port] of a server
<code>lfn</code>	Logical File Name
<code>url</code>	URL of the file as registered in indexing service
<code>service_path</code>	End-point path of the web service
<code>file</code>	File name with full path
<code>option</code>	URL option
<code>metadataoption</code>	Metadata option for indexing service

The following options are supported for location URLs:

<code>threads=&lt;number&gt;</code>	specifies number of parallel streams to be used by GridFTP or HTTP(s,g); default value is 1, maximal value is 10
<code>cache=yes no renew copy</code>	indicates whether the GM should cache the file; default for input files is <b>yes</b> . <b>renew</b> forces a download of the file, even if the cached copy is still valid. <b>copy</b> forces the cached file to be copied (rather than linked) to the session dir, this is useful if for example the file is to be modified ( <b>copy</b> option is available in ARC 0.8.1 and above).
<code>readonly=yes no</code>	for transfers to <code>file://</code> destinations, specifies whether the file should be read-only (unmodifiable) or not; default is <b>yes</b>
<code>secure=yes no</code>	indicates whether the GridFTP data channel should be encrypted; default is <b>no</b>
<code>blocksize=&lt;number&gt;</code>	specifies size of chunks/blocks/buffers used in GridFTP or HTTP(s,g) transactions; default is protocol dependent
<code>checksum=cksum md5 adler32 no</code>	specifies the algorithm for checksum to be computed (for transfer verification or provided to the indexing server). This is overridden by any metadata options specified (see below). If this option is not provided, the default for the protocol is used. <b>checksum=no</b> disables checksum calculation ( <b>adler32</b> and <b>no</b> options are available in ARC 0.8.1 and above).
<code>exec=yes no</code>	means the file should be treated as executable
<code>preserve=yes no</code>	specify if file must be uploaded to this destination even if job processing failed (default is <b>no</b> )
<code>guid=yes no</code>	make software use GUIDs instead of LFNs while communicating to indexing services; meaningful for <code>rls://</code> only
<code>overwrite=yes no</code>	make software try to overwrite existing file(s), i.e. before writing to destination, tools will try to remove any information/content associated with specified URL

<code>protocol=gsi gssapi ssl tls ssl3</code>	to distinguish between different kinds of <code>https/httpg</code> and <code>srn</code> protocols. Here <code>gssapi</code> stands for <code>httpg</code> implementation using only GSSAPI functions to wrap data and <code>gsi</code> uses additional headers as implemented in Globus IO. The <code>ssl</code> and <code>tls</code> stand for usual <code>https</code> and especially usable only if used with <code>srn</code> protocol. The <code>ssl3</code> is mostly same as <code>ssl</code> but uses SSLv3 hadshake while establishing <code>https</code> connection. The default is <code>gssapi</code> for <code>srn</code> connections, <code>tls</code> for <code>https</code> and <code>gssapi</code> for <code>httpg</code> . In case of <code>srn</code> if default fails, <code>gsi</code> is then tried.
<code>spacetoken=&lt;pattern&gt;</code>	specify the space token to be used for uploads to SRM storage elements supporting SRM version 2.2 or higher
<code>autodir=yes no</code>	specify if before writing to specified location software should try to create all directories mentioned in specified URL. Currently this applies to FTP and GridFTP only. Default for those protocols is <code>yes</code>
<code>tcpnodelay=yes no</code>	controls the use of the TCP_NODELAY socket option (which disables the Nagle algorithm). Applies to <code>http(s)</code> only. Default is <code>no</code> (supported only in <code>arc1s</code> and other <code>arc*</code> tools)

Local files are referred to by specifying either a location relative to the job submission working directory, or by an absolute path (the one that starts with `"/`), preceded with a `file://` prefix.

URLs also support metadata options which can be used for registering additional metadata attributes or querying the service using metadata attributes. These options are specified at the end of the LFN and consist of name and value pairs separated by colons. The following attributes are supported:

<code>guid</code>	GUID of the file in the metadata service
<code>checksumtype</code>	Type of checksum. Supported values are <code>cksum</code> (default), <code>md5</code> and <code>adler32</code>
<code>checksumvalue</code>	The checksum of the file

The checksum attributes may also be used to validate files that were uploaded to remote storage.

Examples of URLs are:

```
http://grid.domain.org/dir/script.sh
gsiftp://grid.domain.org:2811;threads=10;secure=yes/dir/input_12378.dat
ldap://grid.domain.org:389/lc=collection1,rc=Nordugrid,dc=nordugrid,dc=org
rls://gsiftp://se.domain.org/datapath/file25.dat@grid.domain.org:61238/myfile02.dat1
file:///home/auser/griddir/steer.cra
lfc://srn://srn.domain.org/griddir@lfc.domain.org/user/file1:guid=\
bc68cdd0-bf94-41ce-ab5a-06a1512764dc:checksumtype=adler32:checksumvalue=123456782
lfc://lfc.domain.org;cache=no/:guid=bc68cdd0-bf94-41ce-ab5a-06a1512764d3
```

<sup>1</sup>This is a destination URL. The file will be copied to the GridFTP server at `se.domain.org` with the path `datapath/file25.dat` and registered in the RLS indexing service at `grid.domain.org` with the LFN `myfile02.dat`.

<sup>2</sup>This is a destination URL. The file will be copied to `srn.domain.org` at the path `griddir/file1` and registered to the LFC service at `lfc.domain.org` with the LFN `/user/file1`. The checksum will be compared to what is reported by the SRM service after the transfer. The given GUID and checksum attributes will also be registered in the LFC.

<sup>3</sup>This is a source URL. The file is registered in the LFC service at `lfc.domain.org` with the given GUID and can be copied or queried by this URL.



## Chapter 4

# ARC Client Configuration

The default behaviour of an ARC client can be configured by specifying alternative values for some parameters in the client configuration file. The file is called `client.conf` and is located in directory `.arc` in user's home area:

```
$HOME/.arc/client.conf
```

If this file is not present or does not contain the relevant configuration information, the global configuration files (if exist) or default values are used instead. Some client tools may be able to create the default `$HOME/.arc/client.conf`, if it does not exist.

The ARC configuration file consists of several configuration blocks. Each configuration block is identified by a keyword and contains configuration options for a specific part of the ARC middleware.

The configuration file is written in a plain text format known as INI. Configuration blocks start with identifying keywords inside square brackets. Typically, first comes a common block: `[common]`. Thereafter follows one or more attribute-value pairs written one on each line in the following format:

```
[common]
attribute1=value1
attribute2=value2
attribute3=value3 value4
# comment line 1
# comment line 2
...
```

Most attributes have counterpart command line options. Command line options always overwrite configuration attributes.

Two blocks are currently recognized, `[common]` and `[alias]`. Following sections describe supported attributes per block.

### 4.1 Block `[common]`

#### **defaultservices**

**This attribute is multi-valued.**

This attribute is used to specify default services to be used. Defining such in the user configuration file will override the default services set in the system configuration.

The value of this attribute should follow the format:

```
service_type:grid:service_url
```

where `service_type` is type of service (e.g. `computing` or `index`), `grid` specifies type of middleware plugin to use when contacting the service (e.g. `ARC0`, `ARC1`, `CREAM`, etc.) and `service_url` is the URL used to contact the service. Several services can be listed, separated with a blank space (no line breaks allowed).

Example:

```
defaultservices=index:ARC0:ldap://index1.ng.org:2135/Mds-Vo-name=testvo,o=grid
└index:ARC1:https://index2.ng.org:50000/isis
└computing:ARC1:https://ce.arc.org:60000/arex
└computing:CREAM:ldap://ce.glite.org:2170/o=grid
```

### rejectservices

**This attribute is multi-valued.**

This attribute can be used to indicate that a certain service should be rejected (“blacklisted”). Several services can be listed, separated with a blank space (no line breaks allowed).

Example: `rejectservices=computing:ARC1:https://bad.service.org/arex`

### verbosity

Default verbosity (debug) level to use for the ARC clients. Corresponds to the `-d` command line option of the clients. Default value is `WARNING`, possible values are `FATAL`, `ERROR`, `WARNING`, `INFO`, `VERBOSE` or `DEBUG`.

Example: `verbosity=INFO`

### timeout

Sets the period of time the client should wait for a service (information, computing, storage etc) to respond when communicating with it. The period should be given in seconds. Default value is 20 seconds. This attribute corresponds to the `-t` command line option.

Example: `timeout=10`

### brokername

Configures which brokering algorithm to use during job submission. This attribute corresponds to the `-b` command line option. The default one is the `Random` broker that chooses targets randomly. Another possibility is, for example, the `FastestQueue` broker that chooses the target with the shortest estimated queue waiting time. For an overview of brokers, please refer to Section 2.2.1.

Example: `brokername=Data`

### brokerarguments



This attribute is used in case a broker comes with arguments. This corresponds to the parameter that follows column in the `-b` command line option.

Example: `brokerarguments=cow`

### joblist

The file storing information about active jobs. This file will be used by commands such as `arcsub`, `arcstat`, `arcsync` etc. to read and write information about jobs. This attribute corresponds to the `-j` command line option. The default location of the file is in the `$HOME/.arc/client.conf` directory with the name `jobs.xml`.

Example:

```
joblist=/home/user/run/jobs.xml
joblist=C:\\run\\jobs.xml
```

### bartender

Specifies default *Bartender* services. Multiple Bartender URLs should be separated with a blank space. These URLs are used by the `chelonia` command line tool, the Chelonia FUSE plugin and by the data tool commands `arccp`, `arcls`, `arcrm`, etc..

Example: `bartender=http://my.bar.com/tender`

### proxypath

Specifies a non-standard location of proxy certificate. It is used by `arcproxy` or similar tools during proxy generation, and all other tools during establishing of a secure connection. This attribute corresponds to the `-P` command line option of `arcproxy`.

Example: `proxypath=/tmp/my-proxy`

### keypath

Specifies a non-standard location of user's private key. It is used by `arcproxy` or similar tools during proxy generation. This attribute corresponds to the `-K` command line option of `arcproxy`.

Example: `keypath=/home/username/key.pem`

### certificatepath

Specifies a non-standard location of user's public certificate. It is used by `arcproxy` or similar tools during proxy generation. This attribute corresponds to the `-C` command line option of `arcproxy`.

Example: `certificatepath=/home/username/cert.pem`

### cacertificatesdirectory

Specifies non-standard location of the directory containing CA-certificates. This attribute corresponds to the `-T` command line option of `arcproxy`.

Example: `cacertificatesdirectory=/home/user/cacertificates`

#### **cacertificatepath**

Specifies an explicit path to the certificate of the CA that issued user's credentials.

Example: `cacertificatepath=/home/user/myCA.0`

#### **vomsserverpath**

Specifies non-standard path to the file which contains list of VOMS services and associated configuration parameters. This attribute corresponds to the `-V` command line option of `arcproxy`.

Example: `vomsserverpath=/etc/voms/vomses`

#### **username**

Sets default username to be used for requesting credentials from Short Lived Credentials Service. This attribute corresponds to the `-U` command line option of `arcslcs`.

Example: `username=johndoe`

#### **password**

Sets default password to be used for requesting credentials from Short Lived Credentials Service. This attribute corresponds to the `-P` command line option of `arcslcs`.

Example: `password=secret`

#### **keypassword**

Sets default password to be used to encode the private key of credentials obtained from a Short Lived Credentials Service. This attribute corresponds to the `-K` command line option of `arcslcs`.

Example: `keypassword=secret2`

#### **keysize**

Sets size (strength) of the private key of credentials obtained from a Short Lived Credentials Service. Default value is 1024. This attribute corresponds to the `-Z` command line option of `arcslcs`.

Example: `keysize=2048`

#### **certificatelifetime**

Sets lifetime (in hours, starting from current time) of user certificate which will be obtained from a Short Lived Credentials Service. This attribute corresponds to the `-L` command line option of `arcslcs`.

Example: `certificatelifetime=12`

**slcs**

Sets the URL to the Short Lived Certificate Service. This attribute corresponds to the `-S` command line option of `arcslcs`.

Example: `slcs=https://127.0.0.1:60000/slcs`

**storedirectory**

Sets directory which will be used to store credentials obtained from a Short Lived Credential Service. This attribute corresponds to the `-D` command line option of `arcslcs`.

Example: `storedirectory=/home/mycredentials`

**jobdownloaddirectory**

Sets directory which will be used as the default job download directory. This attribute corresponds to the `-D` command line option of `arcget`.

Example: `jobdownloaddirectory=/home/myjobs`

**idpname**

Sets Identity Provider name (Shibboleth) to which user belongs. It is used for contacting Short Lived Certificate Services. This attribute corresponds to the `-I` command line option of `arcslcs`.

Example: `idpname=https://idp.testshib.org/idp/shibboleth`

## 4.2 Block [alias]

Users often prefer to submit jobs to a specific site; since contact URLs (and especially end-point references) are very long, it is very convenient to replace them with aliases. Block `[alias]` simply contains a list of alias-value pairs.

Alias substitutions is performed in connection with the `-c` command line switch of the ARC clients.

Aliases can refer to a list of services (separated by a blank space).

Alias definitions can be recursive. Any alias defined in a list that is read before a given list can be used in alias definitions in that list. An alias defined in a list can also be used in alias definitions later in the same list.

Examples:

`[alias]`

```
arc0=computing:ARC0:ldap://ce.ng.org:2135/nordugrid-cluster-name=ce.ng.org,Mds-Vo-name=local,o=grid
arc1=computing:ARC1:https://arex.ng.org:60000/arex
cream=computing:CREAM:ldap://cream.glite.org:2170/o=grid
crossbrokering=arc0 arc1 cream
```

## 4.3 srms.conf

If any data management commands are used with the Storage Resource Management (SRM) [8] protocol, the file

```
$HOME/.arc/srms.conf
```

may be created to store cached information on these services. For more information see the description inside this file.

## 4.4 Deprecated configuration files

ARC configuration file in releases 0.6 and 0.8 has the same name and the same format. Only one attribute is preserved (`timeout`); other attributes unknown to newer ARC versions are ignored.

In  $\text{ARC} \leq 0.5.48$ , configuration was done via files `$HOME/.ngrc`, `$HOME/.nggiislist` and `$HOME/.ngalias`.

The main configuration file `$HOME/.ngrc` could contain user's default settings for the debug level, the information system query timeout and the download directory used by `ngget`. A sample file could be the following:

```
# Sample .ngrc file
# Comments starts with #
NGDEBUG=1
NGTIMEOUT=60
NGDOWNLOAD=/tmp
```

If the environment variables `NGDEBUG`, `NGTIMEOUT` or `NGDOWNLOAD` were defined, these took precedence over the values defined in this configuration. Any command line options override the defaults.

The file `$HOME/.nggiislist` was used to keep the list of default GIIS server URLs, one line per GIIS (see `giis` attribute description above).

The file `$HOME/.ngalias` was used to keep the list of site aliases, one line per alias (see `alias` attribute description above).

## Acknowledgements

This work was supported in parts by: the Nordunet 2 programme, the Nordic DataGrid Facility, the EU KnowARC project (Contract nr. 032691) and the EU EMI project (Grant agreement nr. 261611).

# Bibliography

- [1] gLite, Lightweight Middleware for Grid Computing. URL <http://glite.web.cern.ch/glite/>. Web site.
- [2] A. Anjomshoa et al. Job Submission Description Language (JSDL) Specification, Version 1.0 (first errata update). URL <http://www.gridforum.org/documents/GFD.136.pdf>. GFD-R.136, July 2008.
- [3] Ann L. Chervenak et al. Performance and Scalability of a Replica Location Service. In *Proceedings of the 13th IEEE International Symposium on High Performance Distributed Computing (HPDC'04)*, pages 182–191. IEEE Computer Society Press, 2004. ISBN 0-7803-2175-4.
- [4] M. Ellert, B. Mohn, I. Márton, and G. Rőcsei. *libarcclient – A Client Library for ARC*. The NorduGrid Collaboration. URL [http://www.nordugrid.org/documents/client\\_technical.pdf](http://www.nordugrid.org/documents/client_technical.pdf). NORDUGRID-TECH-20.
- [5] I. Foster and C. Kesselman. Globus: A Metacomputing Infrastructure Toolkit. *International Journal of Supercomputer Applications*, 11(2):115–128, 1997. Available at: <http://www.globus.org>.
- [6] A. Konstantinov. *The ARC Computational Job Management Module – A-REX*. The NorduGrid Collaboration. URL <http://www.nordugrid.org/documents/a-rer.pdf>. NORDUGRID-TECH-14.
- [7] F. Pacini and A. Maraschini. *Job Description Language attributes specification*, 2007. URL <https://edms.cern.ch/document/590869/1>. EGEE-JRA1-TEC-590869-JDL-Attributes-v0-8.
- [8] A. Sim, A. Shoshani, et al. The Storage Resource Manager Interface (SRM) Specification v2.2. URL <http://www.ggf.org/documents/GFD.129.pdf>. GFD-R-P.129, May 2008.
- [9] O. Smirnova. *Extended Resource Specification Language*. The NorduGrid Collaboration. URL <http://www.nordugrid.org/documents/xrsl.pdf>. NORDUGRID-MANUAL-4.
- [10] M. Smith and T. A. Howes. *LDAP : Programming Directory-Enabled Applications with Lightweight Directory Access Protocol*. Macmillan, 1997.

## Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the definition; numbers in roman refer to the pages where the entry is used.

<b>A</b>		arcproxy . . . . .	7	arctest . . . . .	33
arccat . . . . .	14	arcnew . . . . .	19	<b>B</b>	
arcclean . . . . .	18	arcresub . . . . .	21	broker . . . . .	12
arccp . . . . .	24	arcresume . . . . .	20	<b>C</b>	
arcget . . . . .	15	arcrm . . . . .	25	chelonias . . . . .	26
arcinfo . . . . .	17	arcslcs . . . . .	9	credentialDelegation . . . . .	32
arckill . . . . .	17	arcsrmping . . . . .	26	delFile . . . . .	29
arcls . . . . .	23	arcsub . . . . .	9	getFile . . . . .	29
arcmigrate . . . . .	22	arcsync . . . . .	16		

list .....	28	arctest .....	33	keypassword .....	42
makeCollection .....	28	chelonia .....	26	keypath .....	41
makeMountPoint .....	33	credentialDelegation ..	32	keysize .....	42
modify .....	30	delFile .....	29	password .....	42
move .....	29	getFile .....	29	proxypath .....	41
policy .....	30	list .....	28	rejectservices .....	40
putFile .....	29	makeCollection .....	28	slcs .....	42
removeCredentials .....	33	makeMountPoint .....	33	srms.conf .....	43
stat .....	27	modify .....	30	storedirectory .....	43
unlink .....	31	move .....	29	timeout .....	40
unmakeCollection .....	28	policy .....	30	username .....	42
unmakeMountPoint .....	33	putFile .....	29	verbosity .....	40
commands		removeCredentials .....	33	vomsserverpath .....	42
arccat .....	14	stat .....	27		
arcclean .....	18	unlink .....	31	<b>D</b>	
arccp .....	24	unmakeCollection .....	28	data management .....	23
arcget .....	15	unmakeMountPoint .....	33		
arcinfo .....	17	configuration		<b>J</b>	
arckill .....	17	bartender .....	41	job ID .....	11
arcls .....	23	brokerarguments .....	40	job management .....	9
arcmigrate .....	22	brokername .....	40		
arcproxy .....	7	cacertificatepath .....	42	<b>S</b>	
arc renew .....	19	cacertificatesdirectory ..	41	security .....	7
arcresub .....	21	certificatelifetime .....	42	submit job .....	9
arcresume .....	20	certificatepath .....	41		
arcrm .....	25	defaultservices .....	39	<b>U</b>	
arcslcs .....	9	deprecated files .....	44	URL .....	35
arcsrmping .....	26	idpname .....	43	options .....	36
arcs sub .....	9	jobdownloaddirectory .....	43	URLs .....	35
arcsync .....	16	joblist .....	41		