



NORDUGRID-MANUAL-13

30/4/2013

ARC CLIENTS

User Manual for ARC 11.05 (client versions 1.0.0) and above

Contents

1	Introduction	5
2	Commands	7
2.1	Proxy utilities	7
2.1.1	arcproxy	7
2.1.2	arcslcs	9
2.2	Job submission and management	9
2.2.1	arcsb	9
2.2.2	arcstat	14
2.2.3	arccat	15
2.2.4	arcget	16
2.2.5	arcsync	18
2.2.6	arcinfo	19
2.2.7	arckill	19
2.2.8	arcclean	20
2.2.9	arcnew	22
2.2.10	arcresume	23
2.2.11	arcresub	24
2.2.12	arcmigrate	26
2.3	Data manipulation	27
2.3.1	arcls	27
2.3.2	arccp	28
2.3.3	arcrm	29
2.3.4	arcmkdir	30
2.3.5	arcsrmping	30
2.4	Test suite	31
2.4.1	arctest	31
3	URLs	33
4	ARC Client Configuration	37
4.1	Block [common]	38
	defaultservices	38
	rejectservices	38

rejectdiscovery	38
rejectmanagement	38
infointerface	39
submissioninterface	39
verbosity	39
timeout	39
brokername	39
brokerarguments	39
joblist	40
bartender	40
proxypath	40
keypath	40
certificatepath	40
cacertificatesdirectory	41
cacertificatepath	41
vomssserverpath	41
username	41
password	41
keypassword	41
keysize	41
certificatelifetime	42
slcs	42
storedirectory	42
jobdownloaddirectory	42
idpname	42
4.2 Service blocks	42
url	43
default	43
group	43
infointerface	44
submissioninterface	44
registryinterface	44
4.3 srms.conf	44
4.4 Block [alias]	45
4.5 Deprecated configuration files	45

Chapter 1

Introduction

The command line user interface of ARC consists of a set of commands necessary for job submission and manipulation and data management. This manual replaces the older version in `NORDUGRID-MANUAL-1` and is valid for ARC versions 0.9 and above. Command line tools semantics is the same as in earlier versions of ARC, roughly following that of basic Linux commands and most common batch system commands. One obvious difference is change of the legacy prefix from “ng” to the more appropriate “arc”. This is not only a cosmetic change: **behaviour of the commands also have changed**, as did their functionalities and options.

Users are strongly discouraged from modifying their old scripts by simply replacing “ng” with “arc”
– results may be unpredictable.

Chapter 2

Commands

2.1 Proxy utilities

ARC now comes complete with a set of utilities to create temporary user credentials (proxies) used to access Grid services.

2.1.1 arcproxy

In order to contact Grid services (submit jobs, copy data, check information etc), one has to present valid credentials. These are commonly formalized as so-called “proxy” certificates. There are many different types of proxy certificates, with different Grids and different services having own preferences. **arcproxy** is a powerful tool that can be used to generate most commonly used proxies. It supports the following types:

- pre-RFC GSI proxy
- RFC-compliant proxy (default)
- VOMS-extended proxy
- MyProxy delegation

arcproxy requires presence of user’s private key and public certificate, as well as the public certificate of their issuer CA.

arcproxy [options]

Options:

-P, --proxy	<i>path</i>	path to the proxy file
-C, --cert	<i>path</i>	path to the certificate file
-K, --key	<i>path</i>	path to the key file
-T, --cadir	<i>path</i>	path to the trusted certificate directory, only needed for VOMS client functionality
-V, --vomses	<i>path</i>	path to the VOMS server configuration file
-S, --voms	<i>voms[:command]</i>	Specify VOMS server (more than one VOMS server can be specified like this: -voms VOa:command1 -voms VOb:command2)

		:command is optional, and is used to ask for specific attributes(e.g. roles). Command options are:
		all – put all of this DN's attributes into AC;
		list – list all of the DN's attribute,will not create AC extension;
		/Role=yourRole – specify the role, if this DN has such a role, the role will be put into AC
		/voname/groupname/Role=yourRole – specify the VO,group and role; if this DN has such a role, the role will be put into AC
-o, --order	<i>group[:role]</i>	Specify ordering of attributes, Examples:
		-order /knowarc.eu/coredev:Developer,/knowarc.eu/testers:Tester
		-order /knowarc.eu/coredev:Developer,/knowarc.eu/testers:Tester
-G, --gsicom		use GSI communication protocol for contacting VOMS services
-O, --old		use GSI proxy (default is RFC 3820 compliant proxy)
-I, --info		print all information about this proxy. In order to show the Identity (DN without CN as suffix for proxy) of the certificate, the 'trusted certdir' is needed.
-r, --remove		removes the proxy file
-U, --user	<i>string</i>	username for MyProxy server
-L, --myproxysrv	<i>URL</i>	URL of MyProxy server
-M, --myproxycmd	<i>PUT GET</i>	command to MyProxy server. The command can be PUT and GET.
		PUT/put – put a delegated credential to MyProxy server;
		GET/get – get a delegated credential from MyProxy server, credential (certificate and key) is not needed in this case.
-c, --constraint	<i>string</i>	proxy constraints
-t, --timeout	<i>seconds</i>	timeout for network communication, in seconds (default 20 seconds)
-d, --debug	<i>verbosity</i>	verbosity level is one of FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG
-z, --conffile	<i>filename</i>	configuration file (on Linux, default \$HOME/.arc/client.conf)
-v, --version		print version information
-h, --help		print help page

Note that it does not make sense to specify the order of attributes if you have two or more different VOMS servers specified.

MyProxy functionality can be used together with VOMS functionality.

Supported constraints are:

- **validityStart=time** – e.g. 2008-05-29T10:20:30Z; time when certificate becomes valid. Default is now.
- **validityEnd=time** – time when certificate becomes invalid. Default is 43200 (12 hours) from start.

- `validityPeriod=time` – e.g. 43200 or 12h or 12H; for how long certificate is valid. If neither `validityPeriod` nor `validityEnd` are specified, default is 12 hours
- `vomsACvalidityPeriod=time` – e.g. 43200 or 12h or 12H; for how long the AC is valid. Default is the same as `validityPeriod`.
- `proxyPolicy=policy content` – assigns specified string to proxy policy to limit it's functionality.
- `proxyPolicyFile=policy file`

2.1.2 arcslcs

This utility generates short-lived credential based on the credential to IdP in SAML2SSO profile (normally the username/password to Shibboleth IdP).

arcslcs [options]

Options:

<code>-S, --ur;</code>	<i>URL</i>	URL of SLCS Service (e.g. <code>https://127.0.0.1:60000/slcs</code>)
<code>-I, --idp</code>	<i>URL</i>	the name of IdP (e.g. <code>https://idp.testshib.org/idp/shibboleth</code>)
<code>-U, --user</code>	<i>string</i>	User account to IdP
<code>-P, --password</code>	<i>string</i>	password for user account to IdP
<code>-Z, --keysize</code>	<i>integer</i>	size of the private key, default is 1024
<code>-K, --keypass</code>		passphrase for protecting the private key; if not set, the private key file will not be protected by the passphrase.
<code>-L, --lifetime</code>	<i>hours</i>	life time of the credential (hours)), starting with current time
<code>-D, --storedir</code>	<i>path</i>	store directory of the credential
communication, in seconds (default 20 seconds)		
<code>-d, --debug</code>	<i>verbosity</i>	verbosity level is one of FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG
<code>-z, --conffile</code>	<i>filename</i>	configuration file (on Linux, default <code>\$HOME/.arc/client.conf</code>)
<code>-v, --version</code>		print version information
<code>-h, --help</code>		print help page

2.2 Job submission and management

The following commands are used for job submission and management, such as status check, results retrieval, cancellation, re-submission and such. The jobs must be described using a job description language. ARC supports the following languages: JSDL [2], xRSL [9] and JDL [7].

2.2.1 arcsub

The `arcsb` command is the most essential one, as it is used for submitting jobs to the Grid resources. `arcsb` matches user's job description to the information collected from the Grid, and the optimal site is

being selected for job submission. The job description is then being submitted to that site, and usually is then forwarded to a local Resource Management System (LRMS), which can be, e.g., PBS or Condor or SGE etc.

arcsb [options] [filename ...]

Options:

-e, --jobdescrstring	<i>filename</i>	string describing the job to be submitted
-f, --jobdescrfile	<i>filename</i>	file describing the job to be submitted
-j, --joblist	<i>filename</i>	the file storing information about active jobs (on Linux, default <code>\$.arc/jobs.xml</code>)
-o, --jobids-to-file	<i>filename</i>	the IDs of the submitted jobs will be appended to this file
-D, --dryrun		add dryrun option to the job description
-x, --dumpdescription		do not submit – dump transformed job description to stdout
-b, --broker	<i>string</i>	select broker method (default is Random)
-P, --listplugins		list the available plugins
-t, --timeout	<i>seconds</i>	timeout for network communication, in seconds (default 20)
-d, --debug	<i>verbosity</i>	verbosity level, FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG - default WARNING
-z, --conffile	<i>filename</i>	configuration file (on Linux, default <code>\$HOME/.arc/client.conf</code>)
-v, --version		print version information
-h, --help		print help page

Options in ARC 11.05:

-c, --cluster	[-] <i>designator</i>	explicitly select or reject (-) a specific site
-g, --index	[-] <i>designator</i>	explicitly select or reject (-) a specific index server

Options in ARC 12.05:

-c, --cluster	<i>designator</i>	select one or more computing elements by an alias for a single CE, a group of CEs or a URL
-g, --index	<i>designator</i>	select one or more registries by an alias for a single registry, a group of registries or a URL
-R, --rejectdiscovery	<i>URL</i>	skip the service with the given URL during service discovery
-S, --submissioninterface	<i>InterfaceName</i>	only use this interface for submitting (e.g. <code>org.nordugrid.gridftpjob</code> , <code>org.ogf.emies</code> , <code>org.ogf.bes</code>)

Arguments:

filename ...	file(s) describing the job(s) to be submitted
---------------------	---

A typical Grid job submission looks like:

```
arcsb myjob.jsdl
```

Here `myjob.jsdl` is a file containing job description. Note that in this example `-f` is omitted since the job description file is the last item on the command line.

Please remember that you must have **valid credentials** (see Section 2.1) and be authorised at at least one Grid site.

The job must be described using one of the supported job description languages. The description can be entered either as an argument on the command line, or can be read from a file, as in the example above. Several jobs can be requested at the same time by giving more than one file name as an argument, or by repeating the `-f` or `-e` options. It is possible to mix `-e` and `-f` options in the same `arcsub` command.

A simple "Hello World" job description `myjob.jsdl` using the standard JSDL language is shown below.

```
<?xml version="1.0" encoding="UTF-8"?>
<JobDefinition
  xmlns="http://schemas.ggf.org/jSDL/2005/11/jSDL"
  xmlns:posix="http://schemas.ggf.org/jSDL/2005/11/jSDL-posix">
  <JobDescription>
    <JobIdentification>
      <JobName>Hello World job</JobName>
    </JobIdentification>
    <Application>
      <posix:POSIXApplication>
        <posix:Executable>/bin/echo</posix:Executable>
        <posix:Argument>'Hello World'</posix:Argument>
        <posix:Output>out.txt</posix:Output>
        <posix:Error>err.txt</posix:Error>
      </posix:POSIXApplication>
    </Application>
  </JobDescription>
</JobDefinition>
```

If a job is successfully submitted, a **job identifier** (*job ID*) is printed to standard output.

The job ID uniquely identifies the job. Job IDs differ strongly for different computing service flavours, but basically they have a form of a URL. You should use job ID as a handle to refer to the job when doing other job manipulations, such as querying job status (`arcstat`), killing it (`arckill`), re-submitting (`arcresub`), or retrieving the result (`arcget`).

Usually job ID is a valid URL for the job session directory. You can almost always use it to access the files related to the job, by using data management tools (see Chapter 2.3).

There may be exceptions for some computing service flavours like CREAM which do not support listing job session directory.

The `-c` option can be used to manually select known computing sites, for example:

```
arcsub -c alias -c group -c URL job.xrsl
```

This will submit a job to either of the sites known by the alias `alias` or member of the group `group*` or having the URL `URL`.

In ARC 11.05, to submit a job to any site except `badsite`, use `-` sign in front of the name:

```
arcsub -c -badsite job.xrsl
```

See below for description of different kinds of designators which can be used with `-c` and `-g` options in ARC 11.05.

In ARC 12.05, to submit a job to any site except `badsite.example.com`, use the `-R` option with the site's URL (which can be shortened to a domain name):

```
arcsub -R badsite.example.com job.xrsl
```

*groups are only available in ARC 12.05

The **arcsb** command locates the available sites by querying the information system (unless option **-c** is used, in which case only the listed sites are queried). Default index services for the information system are specified in the configuration template distributed with the middleware, and can be overwritten both in the user's configuration (see Section 4) and from the command line using option **-g**. Different Grid middlewares may use different notation for such index services.

In ARC 11.05 (client versions 1.*.*) the designators for **-c** and **-g** are either alias names, group names or URLs. **interface:URL**, where **interface:** is optional, specifying the computing service flavour (and the corresponding plugin) to be used when handling the URL. Possible flavours are:

ARC0 Legacy ARC execution and index services (requires the **nordugrid-arc-plugins-globus** package to be installed)

ARC1 Web service ARC execution service derived from OGSA-BES standard

CREAM CREAM BES-compliant execution service

BES Generic BES plugin consistent with the OGSA-BES standard

EMIES Web service following EMI Execution Service specifications

Here are examples of full designators for ARC legacy index services:

```
ARC0:ldap://ce.ng.eu:2135/nordugrid-cluster-name=ce.ng.eu,Mds-Vo-name=local, o=grid
ARC0:ldap://index.ng.org:2135/mds-vo-name=sweden,O=grid
```

and for CREAM

```
CREAM:ldap://cream.glite.org:2170/o=grid
```

In case *interface:* part is missing every communication protocol/interface corresponding to supported flavours and matching URL will be tried. Because **arcsb** supports multiple Grid flavours and this number is continuously increasing it is strongly advisable not to skip *interface:* part. Example of such designator is

```
ldap://ce.ng.eu:2135/nordugrid-cluster-name=ce.ng.eu,Mds-Vo-name=local,o=grid
```

For convenience it is possible to shorten designator even more by skipping protocol and path parts of URL. So designator may be as simple as hostname of service to be contacted. Here is an example of such shorthand designator for index server

```
index.ng.org/mds-vo-name=sweden
```

and those suitable both for **-c** and **-g** options:

```
cream.glite.org
ce.ng.eu
```

If such short designators are used then rest of the URL is automatically generated according to the flavour which is currently tried. For example in the case of ARC1, **https** communication protocol is assumed.

If you are using some services frequently enough it is recommended to use aliases for these URLs. Aliases are specified in the configuration file (see Section 4).

In ARC 12.05, it is advisable to configure each site in your client configuration (see Section 4.2) and use its alias. Specifying designators (full URLs) on the command line is possible, but not recommended. Flavours as used in ARC 11.05 are not recognised in ARC 12.05. To list possible submission interfaces (to use with **-S** option), use **arcinfo** command.

In order to keep track of submitted jobs, ARC client stores information in a dedicated file, on Linux

platforms by default located in `$HOME/.arc/jobs.xml`. It is sometimes convenient to keep separate lists (e.g., for different kinds of jobs), to be used later with e.g. `arcstat`. This is achieved with the help of the `-j` command line option.

The ARC client transforms input job description into a format that can be understood by the Grid services to which it is being submitted. By specifying the `--dumpdescription` option, such transformed description is written to the standard output instead of being submitted for execution.

Possible broker values for the `arcsub` command line option `-b` are:

- **Random** – ranks targets randomly (default)
- **FastestQueue** – ranks targets according to their queue length
- **Benchmark[:name]** – ranks targets according to a given benchmark, as specified by the **name**. If no benchmark is specified, CINT2000 [†] is used
- **Data** – ranks targets according the amount of megabytes of the requested input files that are already in the computing resources cache.
- **Python:<module>.<class>[:arguments]** – ranks targets using any user-supplied custom Python broker module, optionally with broker arguments. Such module can reside anywhere in user's `PYTHONPATH`
- **<otherbroker>[:arguments]** – ranks targets using any user-supplied custom C++ broker plugin, optionally with broker arguments. Default location for broker plugins on Linux systems is `/usr/lib/arc` (may depend on the operating system), or the one specified by the `ARC_PLUGIN_PATH`.

To write a custom broker in C++ one has to write a new specialization of the **Broker** base class and implement the **SortTargets** method in the new class. The class should be compiled as a loadable module that has the proper ARC plugin descriptor for the new broker. For example, to build a broker plugin “MyBroker” one executes:

```
g++ -I /arc-install/include \
    -L /arc-install/lib \
    'pkg-config --cflags glibmm-2.4 libxml-2.0' \
    -o libacmybroker.so -shared MyBroker.cpp
```

For more details, refer to *libarc* documentation [4].

It often happens that some sites that `arcsub` has to contact are slow to answer, or are down altogether. This will not prevent you from submitting a job, but will slow down the submission. To speed it up, you may want to specify a shorter timeout (default is 20 seconds) with the `-t` option:

```
arcsub -t 5 myjob.jsdl
```

Default value for the timeout can be set in the user's configuration file (see Section 4).

If you would like to get diagnostics of the process of resource discovery and requirements matching, a very useful option is `-d`. The following command:

```
arcsub -d VERBOSE myjob.xrsl
```

will print out the steps taken by the ARC client to find the best cluster satisfying your job requirements. Possible diagnostics levels, in the order of increasing verbosity, are: **FATAL**, **ERROR**, **WARNING**, **INFO**, **VERBOSE** and **DEBUG**. Default is **WARNING**, and it can be set to another value in the user's configuration file.

Default configuration file on Linux platforms is `$HOME/.arc/client.conf`. However, a user can choose any other pre-defined configuration through option `-z`.

Command line option `-v` prints out version of the installed ARC client package, and option `-h` provides a short help text.

[†]<http://www.spec.org/cpu2000/CINT2000/>

For certain advanced computational jobs which may need to communicate their status to some external services, there may be a need for knowing internal job ID. For jobs accepted by ARC computational services this information can be found in the local (for the job executable) environment variable `GRID_GLOBAL_JOBID`. One needs to take into account that this ID is probably different from the one provided by `arcsub`. An example is an ID provided by the A-REX computing service. That service provides OGSA-BES compatible interface for job management and the ID contains an XML document compliant with OGSA-BES specifications.

2.2.2 arcstat

arcstat [options] [job ...]

Options:

-a, --all		all jobs
-j, --joblist	<i>filename</i>	the file storing information about active jobs (on Linux, default <code>\$HOME/.arc/jobs.xml</code>)
-i, --jobids-from-file	<i>filename</i>	file containing a list of job IDs
-s, --status	<i>statusstr</i>	only select jobs whose status is <i>statusstr</i>
-l, --long		long format (extended information)
-S, --sort	<i>criterion</i>	sort jobs according to job ID (criterion <i>jobid</i>), submission time (<i>submissiontime</i>) or job name (<i>job-name</i>)
-R, --rsort	<i>criterion</i>	reverse sorting of jobs according to job ID, submission time or job name
-p, --print-jobids		instead of the status only the IDs of the selected jobs will be printed
-P, --listplugins		list the available plugins
-t, --timeout	<i>time</i>	timeout for queries (default 20 sec)
-d, --debug	<i>verbosity</i>	verbosity level is one of FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG
-z, --conffile	<i>filename</i>	configuration file (on Linux, default <code>\$HOME/.arc/client.conf</code>)
-v, --version		print version information
-h, --help		print help page

Options in ARC 11.05:

-c, --cluster	[-]name	explicitly select or reject a specific site
----------------------	----------------	---

Options in ARC 12.05:

-c, --cluster	<i>designator</i>	select one or more computing elements by an alias for a single CE, a group of CEs or a URL
-r, --rejectmanagement	<i>URL</i>	skip jobs which are on a computing element with a given URL

Arguments:

job ...	list of job IDs and/or job names
----------------	----------------------------------

The `arcstat` command returns the status of jobs in the Grid, and is typically issued with a job ID (as returned by `arcsub`) as an argument. It is also possible to use job name instead of ID, but if several jobs have identical names, information will be collected about all of them. More than one job ID and/or

name can be given.

When several of the `-c <cluster>`, `-i <jobidfile>` and `[job...]` command line options are specified, the command returns information about all jobs listed on the command line plus all jobs on the specified clusters plus all jobs from the specified `jobidfile`.

However the `-c <cluster>` (for ARC 11.05), `-r <URL>` (for ARC 12.05) and `-s <status>` options will filter the jobs selected by the above mentioned options, or if none of those are specified, then these will filter all the jobs.

For example, `arcstat -s Finished -c mycluster <jobid>` will return information about the finished jobs on `mycluster` plus about `<jobid>` but only if it is finished. Or, `arcstat -i jobidfile -r mycluster.example.com` will return information about jobs which are in the `jobidfile` but not on `mycluster.example.com`.

If the `-l` option is given, extended information is printed.

Jobs can be sorted according to the job ID, submission time or job name, either in normal or reverse order. By using the `--sort` or `--rsort` option followed by the desired ordering (`jobid`, `submissiontime` or `jobname`, respectively), jobs will be sorted in normal or reverse order. Note that the options `--sort` and `--rsort` cannot be used at the same time.

Options `-a`, `-c`, `-s` and `-j` do not use job ID or names. By specifying the `-a` option, the status of all active jobs will be shown. If the `-j` option is used, the list of jobs is read from a file with the specified filename, instead of the default one (`$HOME/.arc/jobs.xml`) (on Linux).

Option `-c` accepts arguments as explained in the description of `arcsub`, that is, in the `GRID:URL` notation for ARC 11.05, or URLs, aliases and groups from the configuration file in ARC 12.05.

Different sites may report different job states, depending on the installed grid middleware version. Typical values can be e.g. “Accepted”, “Preparing”, “Running”, “Finished” or “Deleted”. Please refer to the respective middleware documentation for job state model description.

Command line option `-s` will instruct the client to display information of only those jobs which status matches the instruction. This option must be given together with either `-a` or `-c` ones, e.g.:

```
arcstat -as Finished
```

Other command line options are identical to those of `arcsub`.

2.2.3 arccat

It is often useful to monitor the job progress by checking what it prints on the standard output or error. The command `arccat` assists here, extracting the corresponding information from the execution cluster and dumping it on the user’s screen. It works both for running tasks and for the finished ones. This allows a user to check the output of the finished task without actually retrieving it.

arccat [options] [job ...]

Options:

<code>-a, --all</code>		all jobs
<code>-j, --joblist</code>	<i>filename</i>	the file storing information about active jobs (default <code>/.arc/jobs.xml</code>)
<code>-i, --jobids-from-file</code>	<i>filename</i>	file containing a list of job IDs
<code>-s, --status</code>	<i>statusstr</i>	only select jobs whose status is <i>statusstr</i>
<code>-o, --stdout</code>		show the stdout of the job (default)

<code>-e, --stderr</code>		show the stderr of the job
<code>-l, --joblog</code>		show the CE's error log of the job
<code>-P, --listplugins</code>		list the available plugins
<code>-t, --timeout</code>	<i>time</i>	timeout for queries (default 20 sec)
<code>-d, --debug</code>	<i>verbosity</i>	verbosity level is one of FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG
<code>-z, --conffile</code>	<i>filename</i>	configuration file (on Linux, default \$HOME/.arc/client.conf)
<code>-v, --version</code>		print version information
<code>-h, --help</code>		print help page
<i>Options in ARC 11.05:</i>		
<code>-c, --cluster</code>	<code>[-] url</code>	explicitly select or reject (-) a specific site
<i>Options in ARC 12.05:</i>		
<code>-c, --cluster</code>	<i>designator</i>	select one or more computing elements by an alias for a single CE, a group of CEs or a URL
<code>-r, --rejectmanagement</code>	<i>URL</i>	skip jobs which are on a computing element with a given URL
Arguments:		
<code>job ...</code>		list of job IDs and/or job names

The `arccat` command returns the standard output of a job (`-o` option), the standard error (`-e` option) or errors reported by either Grid Manager or A-REX (`-l` option).

Other command line options have the same meaning as in `arcstat`.

When several of the `-c <cluster>`, `-i <jobidfile>` and `[job...]` command line options are specified, the command prints logs of all jobs listed on the command line plus all jobs on the specified clusters plus all jobs from the specified `jobidfile`.

However the `-c -<cluster>` (for ARC 11.05), `-r <URL>` (for ARC 12.05) and `-s <status>` options will filter the jobs selected by the above mentioned options, or if none of those are specified, then these will filter all the jobs.

For example, `arccat -s Finished -c mycluster <jobid>` will print logs of the finished jobs on `mycluster` plus of `<jobid>` but only if it is finished. Or, `arccat -i jobidfile -r mycluster.example.org` will print logs of jobs which are in the `jobidfile` but not on `mycluster.example.org`.

2.2.4 arcget

To retrieve the results of a finished job, the `arcget` command should be used. It will transfer the files specified for download in job description to the user's computer.

arcget [options] [job ...]

Options:

<code>-a, --all</code>		all jobs
<code>-j, --joblist</code>	<i>filename</i>	the file storing information about active jobs (default /.arc/jobs.xml)

-i, --jobids-from-file	<i>filename</i>	file containing a list of job IDs
-s, --status	<i>statusstr</i>	only select jobs whose status is <i>statusstr</i>
-D, --dir	<i>dirname</i>	download path (the job directory will be created in that location)
-J, --usejobname	<i>dirname</i>	use the job name instead of the short ID as the job directory name
-k, --keep		keep files in the Grid (do not clean)
-f, --force		force download (overwrite existing job directory)
-P, --listplugins		list the available plugins
-t, --timeout	<i>time</i>	timeout for queries (default 20 sec)
-d, --debug	<i>verbosity</i>	verbosity level is one of FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG
-z, --conffile	<i>filename</i>	configuration file (on Linux, default \$HOME/.arc/client.conf)
-v, --version		print version information
-h, --help		print help page

Options in ARC 11.05:

-c, --cluster	[-] name	explicitly select or reject a specific site (cluster)
----------------------	-----------------	---

Options in ARC 12.05:

-c, --cluster	<i>designator</i>	select one or more computing elements by an alias for a single CE, a group of CEs or a URL
-r, --rejectmanagement	<i>URL</i>	skip jobs which are on a computing element with a given URL

Arguments:

job ... list of job IDs and/or job names

Only the results of jobs that have finished can be downloaded. Just like in **arcstat** and **arccat** cases, the job can be referred to either by the job ID that was returned by **arcsub** at submission time, or by its name, if the job description contained a job name attribute.

By default, the job is downloaded into a newly created directory in the current path, with the name typically being a large random string. In order to instruct **arcget** to use another path, use option **-D** (note the capital “D”), e.g.

```
arcget -D /tmp/myjobs "Test job nr 1"
```

After downloading, your jobs will be erased from the execution site! Use command line option **-k** to keep finished jobs in the Grid.

Other command line options are identical to those of e.g. **arcstat**.

When several of the **-c <cluster>**, **-i <jobidfile>** and **[job...]** command line options are specified, the command retrieves all jobs listed on the command line plus all jobs on the specified clusters plus all jobs from the specified **jobidfile**.

However the **-c -<cluster>** (for ARC 11.05), **-r <URL>** (for ARC 12.05) and **-s <status>** options will filter the jobs selected by the above mentioned options, or if none of those are specified, then these will filter all the jobs.

For example, **arcget -s Finished -c mycluster <jobid>** will retrieve the finished jobs on **mycluster** plus **<jobid>** but only if it is finished. Or,

```
arcget -i jobidfile -r mycluster.example.org will retrieve jobs which are in the jobidfile
but not on mycluster.example.org.
```

2.2.5 arcsync

It is advised to start every grid session by running **arcsync**, especially when changing workstations. The reason is that your job submission history is cached on your machine, and if you are using ARC client installations on different machines, your local lists of submitted jobs will be different. To synchronise these lists with the information in the Information System, use the **arcsync** command.

arcsync [options]

Options:

-j, --joblist	<i>filename</i>	the file storing information about active jobs (default <code>/.arc/jobs.xml</code>)
-f, --force		don't ask for confirmation
-T, --truncate		truncate the job list before synchronising
-P, --listplugins		list the available plugins
-t, --timeout	<i>seconds</i>	timeout for network communication, in seconds (default 20)
-d, --debug	<i>verbosity</i>	verbosity level, FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG - default WARNING
-z, --conffile	<i>filename</i>	configuration file (on Linux, default <code>\$HOME/.arc/client.conf</code>)
-v, --version		print version information
-h, --help		print help page

Options in ARC 11.05:

-c, --cluster	[<i>-</i>] <i>name</i>	explicitly select or reject a specific site
-g, --index	<i>url</i>	explicitly select or reject (<i>-</i>) a specific index server

Options in ARC 12.05:

-c, --cluster	<i>designator</i>	select one or more computing elements by an alias for a single CE, a group of CEs or a URL
-g, --index	<i>designator</i>	select one or more registries by an alias for a single registry, a group of registries or a URL
-R, --rejectdiscovery	<i>URL</i>	skip the service with the given URL during service discovery

The ARC client keeps a local list of jobs in the user's home directory. If this file is lost, corrupt, or the user wants to recreate the file on a different workstation, the **arcsync** command will recreate this file from the information available in the Information System.

Since the information about a job retrieved from a cluster can be slightly out of date if the user very recently submitted or removed a job, a warning is issued when this command is run. The **-f** option disables this warning.

If the job list is not empty when invoking synchronisation, the old jobs will be merged with the new jobs, unless the **-T** option is given (note the capital "T"), in which case the job list will first be truncated and then the new jobs will be added.

2.2.6 arcinfo

The `arcinfo` command is used to obtain status information about clusters on the Grid.

arcinfo [options]

Options:

<code>-l, --long</code>		long format (extended information)
<code>-P, --listplugins</code>		list the available plugins
<code>-t, --timeout</code>	<i>seconds</i>	timeout for network communication, in seconds (default 20)
<code>-d, --debug</code>	<i>verbosity</i>	verbosity level, FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG - default WARNING
<code>-z, --conffile</code>	<i>filename</i>	configuration file (on Linux, default \$HOME/.arc/client.conf)
<code>-v, --version</code>		print version information
<code>-h, --help</code>		print help page

Options in ARC 11.05:

<code>-c, --cluster</code>	<code>[-] name</code>	explicitly select or reject a specific site
<code>-g, --index</code>	<i>url</i>	explicitly select or reject (-) a specific index server

Options in ARC 12.05:

<code>-c, --cluster</code>	<i>designator</i>	select one or more computing elements by an alias for a single CE, a group of CEs or a URL
<code>-g, --index</code>	<i>designator</i>	select one or more registries by an alias for a single registry, a group of registries or a URL
<code>-R, --rejectdiscovery</code>	<i>URL</i>	skip the service with the given URL during service discovery
<code>-S, --submissioninterface</code>	<i>InterfaceName</i>	only get information about execution targets which supports this job submission interface (e.g. org.nordugrid.gridftpjob, org.ogf.emies, org.ogf.bes)

The `arcinfo` command is used to obtain information about clusters and queues (*targets*) available on the Grid. Either the `--cluster` or `--index` flag should be used to specify the target(s) which should be queried for information. Both of these flags take a service endpoint as argument. See `arcsub` and the configuration notes in Section 4 for description of these.

Detailed information about queried computing services can be obtained by specifying the `--long` flag.

When specifying the `--index` flag, the information about the computing services registered at the index server will be queried, rather than the status of the index server itself.

2.2.7 arckill

It happens that a user may wish to cancel a job. This is done by using the `arckill` command. A job can be killed almost at any stage of processing through the Grid.

arckill [options] [job ...]

Options:

-a, --all		all jobs
-j, --joblist	<i>filename</i>	the file storing information about active jobs (default <code>/.arc/jobs.xml</code>)
-i, --jobids-from-file	<i>filename</i>	file containing a list of job IDs
-s, --status	<i>statusstr</i>	only select jobs whose status is <i>statusstr</i>
-k, --keep		keep files in the Grid (do not clean)
-P, --listplugins		list the available plugins
-t, --timeout	<i>time</i>	timeout for queries (default 20 sec)
-d, --debug	<i>verbosity</i>	verbosity level is one of FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG
-z, --conffile	<i>filename</i>	configuration file (on Linux, default <code>\$HOME/.arc/client.conf</code>)
-v, --version		print version information
-h, --help		print help page

Options in ARC 11.05:

-c, --cluster	[-] url	explicitly select or reject (-) a specific site
----------------------	----------------	---

Options in ARC 12.05:

-c, --cluster	<i>designator</i>	select one or more computing elements by an alias for a single CE, a group of CEs or a URL
-r, --rejectmanagement	<i>URL</i>	skip jobs which are on a computing element with a given URL

Arguments:

job ...	list of job IDs and/or job names
----------------	----------------------------------

If a job is killed, its traces are being cleaned from the Grid. If you wish to keep the killed job in the system, e.g. for a post-mortem analysis, use the **-k** option.

Job cancellation is an asynchronous process, such that it may take a few minutes before the job is actually cancelled.

Command line options have the same meaning as the corresponding ones of **arcstat** and others.

When several of the **-c <cluster>**, **-i <jobidfile>** and **[job...]** command line options are specified, the command kills all jobs listed on the command line plus all jobs on the specified clusters plus all jobs from the specified *jobidfile*.

However the **-c <cluster>** (for ARC 11.05), **-r <URL>** (for ARC 12.05) and **-s <status>** options will filter the jobs selected by the above mentioned options, or if none of those are specified, then these will filter all the jobs.

For example, **arckill -s INLRMS:R -c mycluster <jobid>** will kill the running jobs on *mycluster* plus *<jobid>* but only if it is running. Or, **arckill -i jobidfile -r mycluster.example.com** will kill all jobs which are in the *jobidfile* but not on *mycluster.example.com*.

2.2.8 arcclean

If a job fails or gets killed with **-k** option, or when you are not willing to retrieve the results for some reasons, a good practice for users is not to wait for the system to clean up the job leftovers, but to use

arcclean to release the disk space and to remove the job ID from the list of submitted jobs and from the Information System.

arcclean [options] [job ...]

Options:

-a, --all		all jobs
-j, --joblist	<i>filename</i>	the file storing information about active jobs (default <code>/.arc/jobs.xml</code>)
-i, --jobids-from-file	<i>filename</i>	file containing a list of job IDs
-s, --status	<i>statusstr</i>	only select jobs whose status is <i>statusstr</i>
-f, --force		removes the job ID from the local list even if the job is not found on the Grid
-P, --listplugins		list the available plugins
-t, --timeout	<i>time</i>	timeout for queries (default 20 sec)
-d, --debug	<i>verbosity</i>	verbosity level is one of FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG
-z, --conffile	<i>filename</i>	configuration file (on Linux, default <code>\$HOME/.arc/client.conf</code>)
-v, --version		print version information
-h, --help		print help page

Options in ARC 11.05:

-c, --cluster	[-] name	explicitly select or reject a specific site (cluster)
----------------------	-----------------	---

Options in ARC 12.05:

-c, --cluster	<i>designator</i>	select one or more computing elements by an alias for a single CE, a group of CEs or a URL
-r, --rejectmanagement	<i>URL</i>	skip jobs which are on a computing element with a given URL

Arguments:

job ...	list of job IDs and/or job names
----------------	----------------------------------

Only jobs that have finished or were cancelled can be cleaned.

It happens ever so often that the job is cleaned by the system, or is otherwise unreachable, and yet your local job list file still has it listed. Use **-s** option with value **Undefined** to remove such stale job information from the local list. Note that specifying **-a** and **-f** options together also removes such stale job information, while also removing finished and cancelled jobs.

Other command line options have the same meaning as the corresponding ones of **arcstat** and others.

When several of the **-c <cluster>**, **-i <jobidfile>** and **[job...]** command line options are specified, the command cleans all jobs listed on the command line plus all jobs on the specified clusters plus all jobs from the specified **jobidfile**.

However the **-c -<cluster>** (for ARC 11.05), **-r <URL>** (for ARC 12.05) and **-s <status>** options will filter the jobs selected by the above mentioned options, or if none of those are specified, then these will filter all the jobs.

For example, **arcclean -s FAILED -c mycluster <jobid>** will clean the failed jobs on **mycluster** plus **<jobid>** but only if it is failed. Or, **arcclean -i jobidfile -r mycluster.example.com** will

clean all jobs which are in the `jobidfile` but not on `mycluster.example.com`.

2.2.9 arc renew

Quite often, the user proxy expires while the job is still running (or waiting in a queue). In case such job has to upload output files to a Grid location (a storage element), it will fail. By using the **arc renew** command, users can upload a new proxy to the job. This can be done while a job is still running, thus preventing it from failing

If a job has failed in file upload due to expired proxy, **arc renew** can be issued within 24 hours (or whatever is the expiration time set by the site) after the job end, which must be followed by **arc resume**. The Grid Manager or A-REX will then attempt to finalize the job by uploading the output files to the desired location.

arc renew [options] [job ...]

Options:

-a, --all		all jobs
-j, --joblist	<i>filename</i>	the file storing information about active jobs (default <code>/.arc/jobs.xml</code>)
-i, --jobids-from-file	<i>filename</i>	file containing a list of job IDs
-s, --status	<i>statusstr</i>	only select jobs whose status is <i>statusstr</i>
-P, --listplugins		list the available plugins
-t, --timeout	<i>time</i>	timeout for queries (default 20 sec)
-d, --debug	<i>verbosity</i>	verbosity level is one of FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG
-z, --conffile	<i>filename</i>	configuration file (on Linux, default <code>\$HOME/.arc/client.conf</code>)
-v, --version		print version information
-h, --help		print help page

Options in ARC 11.05:

-c, --cluster	<i>[-] name</i>	explicitly select or reject a specific site (cluster)
----------------------	-----------------	---

Options in ARC 12.05:

-c, --cluster	<i>designator</i>	select one or more computing elements by an alias for a single CE, a group of CEs or a URL
-r, --rejectmanagement	<i>URL</i>	skip jobs which are on a computing element with a given URL

Arguments:

job ...	list of job IDs and/or job names
----------------	----------------------------------

Prior to using **arc renew**, be sure to actually create the new proxy by running **arc proxy**!

Command line options have the same meaning as the corresponding ones of **arc stat** and others.

When several of the `-c <cluster>`, `-i <jobidfile>` and `[job...]` command line options are specified, the command renews proxies of all jobs listed on the command line plus all jobs on the specified clusters plus all jobs from the specified `jobidfile`.

However the `-c -<cluster>` (for ARC 11.05), `-r <URL>` (for ARC 12.05) and `-s <status>` options will filter the jobs selected by the above mentioned options, or if none of those are specified, then these will filter all the jobs.

For example, `arcnew -s FAILED -c mycluster <jobid>` will renew proxies of the failed jobs on `mycluster` plus `<jobid>` but only if it is failed. Or, `arcnew -i jobidfile -r mycluster.example.com` will renew proxies of all jobs which are in the `jobidfile` but not on `mycluster.example.com`.

2.2.10 arcresume

In some cases a user may want to restart a failed job, for example, when input files become available, or the storage element for the output files came back online, or when a proxy is renewed with `arcnew`. This can be done using the `arcresume` command.

Make sure your proxy is still valid, or when uncertain, run `arcproxy` followed by `arcnew` before `arcresume`. The job will be resumed from the state where it has failed.

arcresume [options] [job ...]

<code>-a, --all</code>		all jobs
<code>-j, --joblist</code>	<i>filename</i>	the file storing information about active jobs (default <code>/.arc/jobs.xml</code>)
<code>-i, --jobids-from-file</code>	<i>filename</i>	file containing a list of job IDs
<code>-s, --status</code>	<i>statusstr</i>	only select jobs whose status is <i>statusstr</i>
<code>-P, --listplugins</code>		list the available plugins
<code>-t, --timeout</code>	<i>time</i>	timeout for queries (default 20 sec)
<code>-d, --debug</code>	<i>verbosity</i>	verbosity level is one of FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG
<code>-z, --conffile</code>	<i>filename</i>	configuration file (on Linux, default <code>\$HOME/.arc/client.conf</code>)
<code>-v, --version</code>		print version information
<code>-h, --help</code>		print help page
<i>Options in ARC 11.05:</i>		
<code>-c, --cluster</code>	<code>[-]name</code>	explicitly select or reject a specific site (cluster)
<i>Options in ARC 12.05:</i>		
<code>-c, --cluster</code>	<i>designator</i>	select one or more computing elements by an alias for a single CE, a group of CEs or a URL
<code>-r, --rejectmanagement</code>	<i>URL</i>	skip jobs which are on a computing element with a given URL

Arguments:

`job ...` list of job IDs and/or job names

Command line options have the same meaning as the corresponding ones of **arcstat** and others.

When several of the **-c <cluster>**, **-i <jobidfile>** and **[job...]** command line options are specified, the command resumes all jobs listed on the command line plus all jobs on the specified clusters plus all jobs from the specified **jobidfile**.

However the **-c -<cluster>** (for ARC 11.05), **-r <URL>** (for ARC 12.05) and **-s <status>** options will filter the jobs selected by the above mentioned options, or if none of those are specified, then these will filter all the jobs.

For example, **arcresume -s FAILED -c mycluster <jobid>** will resume the failed jobs on mycluster plus <jobid> but only if it is failed. Or, **arcresume -i jobidfile -r mycluster.example.com** will resume all jobs which are in the **jobidfile** but not on **mycluster.example.com**.

2.2.11 arcresub

Quite often it happens that a user would like to re-submit a job, but has difficulties recovering the original job description file (e.g. the xRSL file). This happens when job description files are created by scripts on-fly, and matching of job description to the job ID is not straightforward. The utility called **arcresub** helps in such situations, allowing users to resubmit jobs.

arcresub [options] [job ...]

Options:

-a, --all		all jobs
-j, --joblist	<i>filename</i>	the file storing information about active jobs (default <code>/.arc/jobs.xml</code>)
-i, --jobids-from-file	<i>filename</i>	file containing a list of job IDs
-o, --jobids-to-file	<i>filename</i>	the IDs of the submitted jobs will be appended to this file
-m, --same		re-submit to the same site
-M, --not-same		do not resubmit to the same cluster
-s, --status	<i>statusstr</i>	only select jobs whose status is <i>statusstr</i>
-x, --dumpdescription		do not submit – dump transformed job description to stdout
-k, --keep		keep files in the Grid (do not clean)
-b, --broker	<i>string</i>	select broker method (default is Random)
-P, --listplugins		list the available plugins
-t, --timeout	<i>time</i>	timeout for queries (default 20 sec)
-d, --debug	<i>verbosity</i>	verbosity level is one of FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG
-z, --conffile	<i>filename</i>	configuration file (on Linux, default <code>\$HOME/.arc/client.conf</code>)
-v, --version		print version information
-h, --help		print help page
<i>Options in ARC 11.05:</i>		
-g, --index	<i>url</i>	explicitly select or reject (-) a specific index server
-c, --cluster	[-] <i>name</i>	explicitly select or reject a specific source site

<code>-q, --qluster</code>	<code>[-]name</code>	explicitly select or reject a specific site as re-submission target
<i>Options in ARC 12.05:</i>		
<code>-g, --index</code>	<i>designator</i>	select one or more registries by an alias for a single registry, a group of registries or a URL
<code>-c, --cluster</code>	<i>designator</i>	select one or more computing elements by an alias for a single CE, a group of CEs or a URL
<code>-q, --qluster</code>	<i>designator</i>	select one or more computing elements for the new jobs by an alias for a single CE, a group of CEs or a URL
<code>-r, --rejectmanagement</code>	<i>URL</i>	skip jobs which are on a computing element with a given URL
<code>-R, --rejectdiscovery</code>	<i>URL</i>	skip the service with the given URL during service discovery
Arguments:		
<code>job ...</code>		list of job IDs and/or job names

More than one job ID and/or job name can be given. If several jobs were submitted with the same job name all those jobs will be resubmitted.

If the job description of a job to be resubmitted, contained any local input files, checksums of these was calculated and stored in the job list, and those will be used to check whether the files has changed. If local input files has changed the job will not be resubmitted.

In case the job description is not found in the job list, an attempt will be made to retrieve it from the cluster holding the original job. This however may fail, since both the submission client and the cluster can have made modifications to the job description.

Upon resubmission the job will receive a new job ID, and the old job ID will be stored in the local job list file, enabling future back tracing of the resubmitted job.

Upon resubmission the job will receive a new job ID. The old job ID will be kept in the local job list file, enabling future back tracing of the resubmitted job.

Regarding command line options, `arcresub` behaves much like `arcsub`, except that `-c` in this case indicates not the submission target site, but on the contrary, the **site from which the jobs will be resubmitted**. Submission target site is specified with option `-q`. If you wish to re-submit each job to the same site, use option `-m`.

If the original job was successfully killed, its traces will be removed from the execution site, unless the `-k` option is specified.

When several of the `-c <cluster>`, `-i <jobidfile>` and `[job...]` command line options are specified, the command resubmits all jobs listed on the command line plus all jobs on the specified clusters plus all jobs from the specified `jobidfile`.

However the `-c -<cluster>` (for ARC 11.05), `-r <URL>` (for ARC 12.05) and `-s <status>` options will filter the jobs selected by the above mentioned options, or if none of those are specified, then these will filter all the jobs.

For example, `arcresub -s FAILED -c mycluster <jobid>` will resubmit the running jobs on `mycluster` plus `<jobid>` but only if it is failed. Or, `arcresub -i jobidfile -r mycluster.example.org` will resubmit all jobs which are in the `jobidfile` but not on `mycluster.example.org`.

2.2.12 arcmigrate

Quite often jobs end up stuck in long queues, and users wish to migrate them to a better resource. Command `arcmigrate` is triggering this migration. It applies only to jobs submitted to the web service interface of A-REX, as other Grid execution services do not support this functionality.

arcmigrate [options] [job ...]

Options:

<code>-f, --force</code>		force migration, ignoring kill failure
<code>-k, --keep</code>		keep the files on the server (do not clean)
<code>-a, --all</code>		all jobs
<code>-b, --broker</code>	<i>string</i>	select broker method (default is Random)
<code>-o, --jobids-to-file</code>	<i>filename</i>	the IDs of the submitted jobs will be appended to this file
<code>-i, --jobids-from-file</code>	<i>filename</i>	file containing a list of job IDs
<code>-j, --joblist</code>	<i>filename</i>	the file storing information about active jobs (default <code>/.arc/jobs.xml</code>)
<code>-z, --conffile</code>	<i>filename</i>	configuration file (on Linux, default <code>\$HOME/.arc/client.conf</code>)
<code>-t, --timeout</code>	<i>time</i>	timeout for queries (default 20 sec)
<code>-P, --listplugins</code>		list the available plugins
<code>-d, --debug</code>	<i>verbosity</i>	verbosity level is one of FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG
<code>-v, --version</code>		print version information
<code>-h, --help</code>		print help page

Options in ARC 11.05:

<code>-c, --cluster</code>	<code>[-] name</code>	explicitly select or reject a specific site (cluster)
<code>-q, --qluster</code>	<code>[-] name</code>	explicitly select or reject a specific site as re-submission target
<code>-g, --index</code>	<i>url</i>	explicitly select or reject (-) a specific index server

Options in ARC 12.05:

<code>-c, --cluster</code>	<i>designator</i>	select one or more computing elements by an alias for a single CE, a group of CEs or a URL
<code>-q, --qluster</code>	<i>designator</i>	select one or more computing elements for the new jobs by an alias for a single CE, a group of CEs or a URL
<code>-g, --index</code>	<i>designator</i>	select one or more registries by an alias for a single registry, a group of registries or a URL
<code>-r, --rejectmanagement</code>	<i>URL</i>	skip jobs which are on a computing element with a given URL
<code>-R, --rejectdiscovery</code>	<i>URL</i>	skip the service with the given URL during service discovery

Arguments:

<code>job ...</code>	list of job IDs and/or job names
----------------------	----------------------------------

Currently only jobs having the status “Queuing” can be migrated

Command line options `-c` and `-q` are interpreted in the same way as in `arcresub`, namely, `-c` indicates “from” and `-q` – “to” which site the job will be migrated.

If the job(s) is successfully migrated, a new job ID(s) is printed out. This job ID uniquely identifies the job while it is being executed.

When several of the `-c <cluster>`, `-i <jobidfile>` and `[job...]` command line options are specified, the command migrates all jobs listed on the command line plus all jobs on the specified clusters plus all jobs from the specified `jobidfile`.

However the `-c -<cluster>` (for ARC 11.05), `-r <URL>` (for ARC 12.05) and `-s <status>` options will filter the jobs selected by the above mentioned options, or if none of those are specified, then these will filter all the jobs.

For example, `arcmigrate -s FAILED -c mycluster <jobid>` will migrate the running jobs on `mycluster` plus `<jobid>` but only if it is failed. Or, `arcmigrate -i jobidfile -r mycluster.example.com` will resubmit all jobs which are in the `jobidfile` but not on `mycluster.example.com`.

2.3 Data manipulation

ARC provides basic data management tools to copy, create, list and remove files and directories to, from and between Grid storage elements and index services.

2.3.1 arcls

`arcls` is a simple utility that allows to list contents and view some attributes of objects of a specified (by a URL) remote directory.

arcls [options] <URL>

Options:

<code>-l, --long</code>		detailed listing
<code>-L, --locations</code>		detailed listing including URLs from which files can be downloaded
<code>-m, --metadata</code>		display all available metadata
<code>-r, --recursive</code>	<i>recursion_level</i>	operate recursively (if possible) up to specified level (0 - no recursion)
<code>-n, --nolist</code>		show only description of requested object, do not list content of directories (like <code>ls -d</code>).
<code>-c, --checkaccess</code>		check readability of object. Retrieving and showing information about object is suppressed.
<code>-t, --timeout</code>	<i>seconds</i>	timeout for network communication, in seconds (default 20)
<code>-P, --plugins</code>		list the available plugins (protocols supported)
<code>-d, --debug</code>	<i>verbosity</i>	verbosity level, FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG - default WARNING

<code>-z, --conffile</code>	<i>filename</i>	configuration file (on Linux, default \$HOME/.arc/client.conf)
<code>-v, --version</code>		print version information
<code>-h, --help</code>		print help page
Arguments:		
<code>URL</code>		file or directory URL

This tool is very convenient not only because it allows to list files at a Storage Element or records in an indexing service, but also because it can give a quick overview of a job's working directory, which is explicitly given by job ID.

Usage examples can be as follows:

```
arcls -L rls://rls.nordugrid.org:38203/logical_file_name
arcls -l gsiftp://lscf.nbi.dk:2811/jobs/1323842831451666535
arcls srm://grid.uio.no:8446/srm/managerv2?SFN=/johndoe/log2
```

Examples of URLs accepted by this tool can be found in Section 3, though `arcls` won't be able to list a directory at an HTTP server, as they normally do not return directory listings.

2.3.2 arccp

`arccp` is a powerful tool to copy files over the Grid. It is a part of the A-REX, but can be used by the User Interface as well.

arccp [options] <source> <destination>

Options:

<code>-p, --passive</code>		use passive transfer (off by default if secure is on, on by default if secure is not requested)
<code>-n, --nopassive</code>		do not try to force passive transfer
<code>-f, --force</code>		if the destination is an indexing service and not the same as the source and the destination is already registered, then the copy is normally not done. However, if this option is specified the source is assumed to be a replica of the destination created in an uncontrolled way and the copy is done like in case of replication. Using this option also skips validation of completed transfers.
<code>-i, --indicate</code>		show progress indicator. If the transfer time is short then there may be no indicator.
<code>-T, --notransfer</code>		do not transfer file, just register it - destination must be non-existing meta-url
<code>-u, --secure</code>		use secure transfer (insecure by default)
<code>-y, --cache</code>	<i>path</i>	path to local cache (use to put file into cache). See [6] for information on caching.
<code>-r, --recursive</code>	<i>recursion_level</i>	operate recursively (if possible) up to specified level (0 - no recursion)
<code>-R, --retries</code>	<i>number</i>	how many times to retry transfer of every file before failing

-L, --location	<i>URL</i>	physical file to write to when destination is an indexing service. Must be specified for indexing services which do not automatically generate physical locations. Can be specified multiple times - locations will be tried in order until one succeeds.
-t, --timeout	<i>seconds</i>	timeout for network communication, in seconds (default 20)
-P, --plugins		list the available plugins (protocols supported)
-d, --debug	<i>verbosity</i>	verbosity level, FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG - default WARNING
-z, --conffile	<i>filename</i>	configuration file (on Linux, default \$HOME/.arc/client.conf)
-v, --version		print version information
-h, --help		print help page
Arguments:		
source		source URL
destination		destination URL

This command transfers contents of a file between 2 end-points. End-points are represented by URLs or meta-URLs or local file paths. For supported endpoints please refer to Section 3.

arccp can perform multi-stream transfers if **threads** URL option is specified and server supports it.

Source can end with **"/**". In that case, the set of files under source will be copied into destination and destination must also end with **"/**". Destination will be created if it does not exist. If copying deeper than one level is required then **-r** must be used. If destination alone ends with **"/**", it is extended with the part of source after last **"/**", thus allowing users to skip the destination file or directory name if it is meant to be identical to the source.

Usage examples of **arccp** are:

```
arccp gsiftp://lscf.nbi.dk:2811/jobs/1323842831451666535/job.out job.out
arccp http://www.nordugrid.org/data/somefile gsiftp://hathi.hep.lu.se/data/
arccp gsiftp://pgs02.grid.upjs.sk:2811/jobs/13331297786445657047863/ output/
arccp -L srm://srm.host.org;spacetoken=MYTOKEN/my.file.1 my.file \
    lfc://lfc.host.org/grid/my.file
```

2.3.3 arcrm

The **arcrm** command allows users to erase files and directories at any location specified by a valid URL.

arcrm [options] <URL>

Options:

-f, --force		remove logical file name registration even if not all physical instances were removed
-t, --timeout	<i>seconds</i>	timeout for network communication, in seconds (default 20)
-P, --plugins		list the available plugins (protocols supported)
-d, --debug	<i>verbosity</i>	verbosity level, FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG - default WARNING
-z, --conffile	<i>filename</i>	configuration file (on Linux, default \$HOME/.arc/client.conf)

<code>-v, --version</code>	print version information
<code>-h, --help</code>	print help page
Arguments:	
URL	file or directory URL

A convenient use for `arcrm` is to erase the files in a data indexing catalog (LFC, RLS or such), as it will not only remove the physical instance, but also will clean up the database record.

Here is an `arcrm` example:

```
arcrm lfc://grid.uio.no/grid/atlas/AOD_0947.pool.root
```

2.3.4 arcmkdir

The `arcmkdir` command allows users to create directories, if the protocol of the specified URL supports it.

arcmkdir [options] <URL>

Options:	
<code>-p, --parents</code>	make parent directories as needed
<code>-t, --timeout</code> <i>seconds</i>	timeout for network communication, in seconds (default 20)
<code>-P, --plugins</code>	list the available plugins (protocols supported)
<code>-d, --debug</code> <i>verbosity</i>	verbosity level, FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG - default WARNING
<code>-z, --conffile</code> <i>filename</i>	configuration file (on Linux, default \$HOME/.arc/client.conf)
<code>-v, --version</code>	print version information
<code>-h, --help</code>	print help page
Arguments:	
URL	directory to create

`arcrm` creates directories on grid storage elements and indexing services. If the parent directory does not exist and `-p` is not specified, then `arcmkdir` will probably fail, but it depends on the protocol. The permissions on the new directory are the default of the server, or if the protocol requires them to be specified then the directory is only readable/writable/searchable by the user (the equivalent of 700 on a file system).

Example:

```
arcmkdir lfc://grid.uio.no/grid/atlas/newdir
```

2.3.5 arcsrpm ping

The `arcsrpm ping` command is used to quickly test availability of an SRM service, similarly to the `ping` tool in Unix.

arcsrmping [options] <service>

Options:

-t, --timeout	<i>seconds</i>	timeout for network communication, in seconds (default 20)
-d, --debug	<i>verbosity</i>	verbosity level, FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG - default WARNING
-z, --conffile	<i>filename</i>	configuration file (on Linux, default \$HOME/.arc/client.conf)
-v, --version		print version information
-h, --help		print help page

Arguments:

service	A URL to an SRM service
----------------	-------------------------

The **arcsrmping** command is a *ping* client for the SRM service. It sends an SRM ping request to the SRM service and displays the result.

2.4 Test suite

2.4.1 arctest

arctest is a simple utility that tests very basic functionalities of the middleware. It is convenient for:

- first-time users who do not know job description languages and yet want to test e.g. their credentials or client setup,
- system administrators who'd like to quickly test their installations without having to learn job description languages.

The **arctest** utility contains pre-defined test jobs which can be submitted either to a specific test site or to a regular Grid infrastructure. In addition, **arctest** can provide basic information about available user credentials (proxy certificate).

arctest [options]

Options:

-J, --jobid	<i>integer</i>	test job number
-j, --joblist	<i>filename</i>	the file storing information about active jobs (on Linux, default \$/.arc/jobs.xml)
-o, --jobids-to-file	<i>filename</i>	the IDs of the submitted jobs will be appended to this file
-D, --dryrun		add dryrun option to the job description
-x, --dumpdescription		do not submit – dump transformed job description to stdout
-E, --certificate		prints information about available user credentials
-b, --broker	<i>string</i>	select broker method (default is Random)

<code>-t, --timeout</code>	<i>seconds</i>	timeout for network communication, in seconds (default 20)
<code>-d, --debug</code>	<i>verbosity</i>	verbosity level, FATAL, ERROR, WARNING, INFO, VERBOSE or DEBUG - default WARNING
<code>-z, --conffile</code>	<i>filename</i>	configuration file (on Linux, default \$HOME/.arc/client.conf)
<code>-v, --version</code>		print version information
<code>-h, --help</code>		print help page
<i>Options in ARC 11.05:</i>		
<code>-c, --cluster</code>	<code>[-] url</code>	explicitly select or reject (-) a specific site
<code>-g, --index</code>	<code>[-] url</code>	explicitly select or reject (-) a specific index server
<i>Options in ARC 12.05:</i>		
<code>-c, --cluster</code>	<i>designator</i>	select one or more computing elements by an alias for a single CE, a group of CEs or a URL
<code>-g, --index</code>	<i>designator</i>	select one or more registries by an alias for a single registry, a group of registries or a URL
<code>-R, --rejectdiscovery</code>	<i>URL</i>	skip the service with the given URL during service discovery
<code>-S, --submissioninterface</code>	<i>InterfaceName</i>	only use this interface for submitting (e.g. org.nordugrid.gridftpjob, org.ogf.emies, org.nordugrid.xbes)

There are currently three test jobs defined. Once submitted, their results can be inspected and retrieved in a usual manner, using `arccat`, `arcstat`, `arcget` etc..

Test job descriptions:

1. A classical “Hello World” job, printing *hello*, *grid* text to standard output at a remote execution site.
2. Lists all environment variables defined for the Grid user at the remote site (using standard output).
3. Downloads the pre-defined input file from the HTTP server, and produces an output file by copying input with a new name. This job thus demonstrates usage of `inputfiles` and `outputfiles` attributes of job description languages.

`arctest` is complementary to the `arcinfo` utility, which extracts information about Grid resources without submitting test jobs, and to `arcproxy -I`, which provides more detailed information about user credentials.

Chapter 3

URLs

File locations in ARC can be specified both as local file names, and as Internet standard *Uniform Resource Locators (URL)*. There are also some additional URL *options* that can be used.

The following transfer protocols and metadata servers are supported:

ftp	ordinary <i>File Transfer Protocol (FTP)</i>
gsiftp	GridFTP, the Globus [®] -enhanced FTP protocol with security, encryption, etc. developed by The Globus Alliance [5]
http	ordinary <i>Hyper-Text Transfer Protocol (HTTP)</i> with PUT and GET methods using multiple streams
https	HTTP with SSL v3
httpg	HTTP with Globus [®] GSI
ldap	ordinary <i>Lightweight Data Access Protocol (LDAP)</i> [10]
rls	Globus [®] <i>Replica Location Service (RLS)</i> [3]
lfc	LFC catalog and indexing service of EGEE gLite [1]
srn	Storage Resource Manager (SRM) service [8]
arc	for the Chelonia storage service, communicates with Bartenders, the path should be a Logical Name (LN) (supported only in arcls , arcsb and other arc* tools.)
file	local to the host file name with a full path

An URL can be used in a standard form, i.e.

```
protocol://[host[:port]]/file
```

Or, to enhance the performance, it can have additional options:

```
protocol://[host[:port]][;option[;option[...]]/file
```

For a metadata service URL, construction is the following:

```
protocol://[;commonoption[;commonoption]][url[|url[...]]@host[:port]  
[;option[;option[...]]/lfn[:metadataoption[:metadataoption[...]]
```

where the nested URL(s) are physical replicas. Common options apply to all replicas, and options in the metadata service URL only apply to that URL and are not passed to the replicas. This means that if an option is to apply to replicas it must be stated in common options, even if no replicas are given.

In user-level tools, URLs may be expressed in this syntax, or there may simpler ways to construct complex URLs. In particular, command line tools such as `arccp` and the `xRSL` and `JSDL` job description languages provide methods to express URLs in a simpler way.

For Chelonia, the syntax is

```
arc://<LogicalName>[?BartenderURL=<URL>]
```

where the `BartenderURL` may come from the `bartender` parameter of the client configuration file. Note that Chelonia URLs are **not** supported in `ngls`, `ngsub` and other `ng*` tools.

For the SRM service, the syntax is

```
srm://host[:port][;options]/[service_path?SFN=]file
```

Versions 1.1 and 2.2 of the SRM protocol are supported. The default `service_path` is `srm/managerv2` when the server supports v2.2, `srm/managerv1` otherwise.

The URL components are:

<code>host[:port]</code>	Hostname or IP address [and port] of a server
<code>lfn</code>	Logical File Name
<code>url</code>	URL of the file as registered in indexing service
<code>service_path</code>	End-point path of the web service
<code>file</code>	File name with full path
<code>option</code>	URL option
<code>metadataoption</code>	Metadata option for indexing service

The following options are supported for location URLs:

<code>threads=<number></code>	specifies number of parallel streams to be used by GridFTP or HTTP(s,g); default value is 1, maximal value is 10
<code>cache=yes no renew copy check</code>	indicates whether the GM should cache the file; default for input files is yes . renew forces a download of the file, even if the cached copy is still valid. copy forces the cached file to be copied (rather than linked) to the session dir, this is useful if for example the file is to be modified. check forces a check of the permission and modification time against the original source. (copy option is available in ARC 0.8.1 and above, check option is available in ARC 2.0.0 and above).
<code>readonly=yes no</code>	for transfers to <code>file://</code> destinations, specifies whether the file should be read-only (unmodifiable) or not; default is yes
<code>secure=yes no</code>	indicates whether the GridFTP data channel should be encrypted; default is no
<code>blocksize=<number></code>	specifies size of chunks/blocks/buffers used in GridFTP or HTTP(s,g) transactions; default is protocol dependent
<code>checksum=cksum md5 adler32 no</code>	specifies the algorithm for checksum to be computed (for transfer verification or provided to the indexing server). This is overridden by any metadata options specified (see below). If this option is not provided, the default for the protocol is used. checksum=no disables checksum calculation (adler32 and no options are available in ARC 0.8.1 and above).
<code>exec=yes no</code>	means the file should be treated as executable
<code>preserve=yes no</code>	specify if file must be uploaded to this destination even if job processing failed (default is no)

<code>guid=yes no</code>	make software use GUIDs instead of LFNs while communicating to indexing services; meaningful for <code>rls://</code> only
<code>overwrite=yes no</code>	make software try to overwrite existing file(s), i.e. before writing to destination, tools will try to remove any information/content associated with specified URL
<code>protocol=gsi gssapi ssl tls ssl3</code>	to distinguish between different kinds of <code>https/httpg</code> and <code>srn</code> protocols. Here <code>gssapi</code> stands for <code>httpg</code> implementation using only GSSAPI functions to wrap data and <code>gsi</code> uses additional headers as implemented in Globus IO. The <code>ssl</code> and <code>tls</code> stand for usual <code>https</code> and especially usable only if used with <code>srn</code> protocol. The <code>ssl3</code> is mostly same as <code>ssl</code> but uses SSLv3 handshake while establishing <code>https</code> connection. The default is <code>gssapi</code> for <code>srn</code> connections, <code>tls</code> for <code>https</code> and <code>gssapi</code> for <code>httpg</code> . In case of <code>srn</code> if default fails, <code>gsi</code> is then tried.
<code>spac token=<pattern></code>	specify the space token to be used for uploads to SRM storage elements supporting SRM version 2.2 or higher
<code>autodir=yes no</code>	specify if before writing to specified location software should try to create all directories mentioned in specified URL. Currently this applies to FTP and GridFTP only. Default for those protocols is <code>yes</code>
<code>tcpnodelay=yes no</code>	controls the use of the TCP_NODELAY socket option (which disables the Nagle algorithm). Applies to <code>http(s)</code> only. Default is <code>no</code> (supported only in <code>arcls</code> and other <code>arc*</code> tools)
<code>transferprotocol=protocols</code>	specify transfer protocols for meta-URLs such as SRM. Multiple protocols can be specified as a comma-separated list in order of preference.

Local files are referred to by specifying either a location relative to the job submission working directory, or by an absolute path (the one that starts with `"/`), preceded with a `file://` prefix.

URLs also support metadata options which can be used for registering additional metadata attributes or querying the service using metadata attributes. These options are specified at the end of the LFN and consist of name and value pairs separated by colons. The following attributes are supported:

<code>guid</code>	GUID of the file in the metadata service
<code>checksumtype</code>	Type of checksum. Supported values are <code>cksum</code> (default), <code>md5</code> and <code>adler32</code>
<code>checksumvalue</code>	The checksum of the file

The checksum attributes may also be used to validate files that were uploaded to remote storage.

Examples of URLs are:

```
http://grid.domain.org/dir/script.sh
gsiftp://grid.domain.org:2811;threads=10;secure=yes/dir/input_12378.dat
ldap://grid.domain.org:389/lc=collection1,rc=Nordugrid,dc=nordugrid,dc=org
rls://gsiftp://se.domain.org/datapath/file25.dat@grid.domain.org:61238/myfile02.dat1
file:///home/auser/griddir/steer.cra
lfc://srn://srn.domain.org/griddir@lfc.domain.org/user/file1:guid=\
bc68cdd0-bf94-41ce-ab5a-06a1512764dc:checksumtype=adler32:checksumvalue=123456782
lfc://;transferprotocol=https@lfc.domain.org;cache=no:guid=\
e7bd53db-16e9-4e9b-97c4-2f4385fbcd773
```

¹This is a destination URL. The file will be copied to the GridFTP server at `se.domain.org` with the path `datapath/file25.dat` and registered in the RLS indexing service at `grid.domain.org` with the

LFN myfile02.dat.

²This is a destination URL. The file will be copied to `srm.domain.org` at the path `griddir/file1` and registered to the LFC service at `lfc.domain.org` with the LFN `/user/file1`. The checksum will be compared to what is reported by the SRM service after the transfer. The given GUID and checksum attributes will also be registered in the LFC.

³This is a source URL. The file is registered in the LFC service at `lfc.domain.org` with the given GUID and can be copied or queried by this URL. The file will not be cached and if the replicas resolve to SRM URLs, the HTTPS transfer protocol will be requested for those replicas.

Chapter 4

ARC Client Configuration

The default behaviour of an ARC client can be configured by specifying alternative values for some parameters in the client configuration file. The file is called `client.conf` and is located in directory `.arc` in user's home area, e.g., on Linux:

```
$HOME/.arc/client.conf
```

If this file is not present or does not contain the relevant configuration information, the global configuration files (if exist) or default values are used instead. Some client tools may be able to create the default `$HOME/.arc/client.conf` on Linux, if it does not exist.

The ARC configuration file consists of several configuration blocks. Each configuration block is identified by a keyword and contains configuration options for a specific part of the ARC middleware.

The configuration file is written in a plain text format known as INI. Configuration blocks start with identifying keywords inside square brackets. Typically, first comes a common block: `[common]`. Thereafter follows one or more attribute-value pairs written one on each line in the following format:

```
[common]
attribute1=value1
attribute2=value2
attribute3=value3 value4
# comment line 1
# comment line 2
...
```

Most attributes have counterpart command line options. Command line options always overwrite configuration attributes.

Client configuration is **different** for ARC 11.05 (client versions 1.*.*) and ARC 12.05 (client versions 2.*.*).

Newer clients will work with the old configuration. Older clients will not understand most new configuration options.

ARC 11.05 clients recognise two configuration blocks, `[common]` and `[alias]`.

ARC 12.05 still makes use of the `[common]` block, but does not recognise `defaultservices` and `rejectservices` options, instead using `rejectdiscovery`, `rejectmanagement`, `infointerface` and `submissioninterface` options. In addition, each service in ARC 12.05 has its own block: `[registry/<alias>]` for registry services and `[computing/<alias>]` for computing services, where the `<alias>` has to be a unique name for the service (without spaces).

4.1 Block [common]

defaultservices (only in ARC 11.05)

This attribute is multi-valued.

This attribute is used to specify default services to be used. Defining such in the user configuration file will override the default services set in the system configuration.

The value of this attribute should follow the format:

```
service_type:grid:service_url
```

where **service_type** is type of service (e.g. **computing** or **index**), **grid** specifies type of middleware plugin to use when contacting the service (e.g. ARC0, ARC1, CREAM, etc.) and **service_url** is the URL used to contact the service. Several services can be listed, separated with a blank space (no line breaks allowed).

Example:

```
defaultservices=index:ARC0:ldap://index1.ng.org:2135/Mds-Vo-name=testvo,o=grid
└index:ARC1:https://index2.ng.org:50000/isis
└computing:ARC1:https://ce.arc.org:60000/arex
└computing:CREAM:ldap://ce.glite.org:2170/o=grid
```

rejectservices (only in ARC 11.05)

This attribute is multi-valued.

This attribute can be used to indicate that a certain service should be rejected (“blacklisted”). Several services can be listed, separated with a blank space (no line breaks allowed).

Example: `rejectservices=computing:ARC1:https://bad.service.org/arex`

rejectdiscovery (since ARC 12.05)

Domain name of a service which should be rejected during service discovery. Jobs will not be submitted to any interface of that service. Multiple **rejectdiscovery** commands can be used.

Example:

```
rejectdiscovery=bad.server.org
rejectdiscovery=bad2.server.org
```

rejectmanagement (since ARC 12.05)

During job management operations, the jobs belonging to this service will be skipped. Multiple **rejectmanagement** commands can be used.

Example:

```
rejectmanagement=bad.server.org
rejectmanagement=bad2.server.org
```

infointerface (since ARC 12.05)

Default information interface used by service discovery and status query operations. If a service has no **infointerface** specified in its configuration block (see Section 4.2), this will be used by default.

Example:

```
infointerface=org.nordugrid.ldapng
```

submissioninterface (since ARC 12.05)

Default submission interface used by job management operations. If a service has no **submissioninterface** specified in its configuration block (see Section 4.2), this will be used by default.

Example:

```
submissioninterface=org.nordugrid.gridftpjob
```

verbosity

Default verbosity (debug) level to use for the ARC clients. Corresponds to the **-d** command line option of the clients. Default value is **WARNING**, possible values are **FATAL**, **ERROR**, **WARNING**, **INFO**, **VERBOSE** or **DEBUG**.

Example: **verbosity=INFO**

timeout

Sets the period of time the client should wait for a service (information, computing, storage etc) to respond when communicating with it. The period should be given in seconds. Default value is 20 seconds. This attribute corresponds to the **-t** command line option.

Example: **timeout=10**

brokername

Configures which brokering algorithm to use during job submission. This attribute corresponds to the **-b** command line option. The default one is the **Random** broker that chooses targets randomly. Another possibility is, for example, the **FastestQueue** broker that chooses the target with the shortest estimated queue waiting time. For an overview of brokers, please refer to Section 2.2.1.

Example: **brokername=Data**

brokerarguments

This attribute is used in case a broker comes with arguments. This corresponds to the parameter that follows column in the `-b` command line option.

Example: `brokerarguments=cow`

joblist

The file storing information about active jobs. This file will be used by commands such as `arcsub`, `arcstat`, `arcsync` etc. to read and write information about jobs. This attribute corresponds to the `-j` command line option. The default location of the file on Linux platforms is in the `$HOME/.arc/client.conf` directory with the name `jobs.xml`.

Example:

```
joblist=/home/user/run/jobs.xml
joblist=C:\\run\\jobs.xml
```

bartender

Specifies default *Bartender* services. Multiple Bartender URLs should be separated with a blank space. These URLs are used by the `chelon` command line tool, the Chelonia FUSE plugin and by the data tool commands `arccp`, `arcls`, `arcrm`, etc..

Example: `bartender=http://my.bar.com/tender`

proxypath

Specifies a non-standard location of proxy certificate. It is used by `arcproxy` or similar tools during proxy generation, and all other tools during establishing of a secure connection. This attribute corresponds to the `-P` command line option of `arcproxy`.

Example: `proxypath=/tmp/my-proxy`

keypath

Specifies a non-standard location of user's private key. It is used by `arcproxy` or similar tools during proxy generation. This attribute corresponds to the `-K` command line option of `arcproxy`.

Example: `keypath=/home/username/key.pem`

certificatepath

Specifies a non-standard location of user's public certificate. It is used by `arcproxy` or similar tools during proxy generation. This attribute corresponds to the `-C` command line option of `arcproxy`.

Example: `certificatepath=/home/username/cert.pem`

cacertificatesdirectory

Specifies non-standard location of the directory containing CA-certificates. This attribute corresponds to the `-T` command line option of `arcproxy`.

Example: `cacertificatesdirectory=/home/user/cacertificates`

cacertificatepath

Specifies an explicit path to the certificate of the CA that issued user's credentials.

Example: `cacertificatepath=/home/user/myCA.0`

vomsserverpath

Specifies non-standard path to the file which contains list of VOMS services and associated configuration parameters. This attribute corresponds to the `-V` command line option of `arcproxy`.

Example: `vomsserverpath=/etc/voms/vomses`

username

Sets default username to be used for requesting credentials from Short Lived Credentials Service. This attribute corresponds to the `-U` command line option of `arcslcs`.

Example: `username=johndoe`

password

Sets default password to be used for requesting credentials from Short Lived Credentials Service. This attribute corresponds to the `-P` command line option of `arcslcs`.

Example: `password=secret`

keypassword

Sets default password to be used to encode the private key of credentials obtained from a Short Lived Credentials Service. This attribute corresponds to the `-K` command line option of `arcslcs`.

Example: `keypassword=secret2`

keysize

Sets size (strength) of the private key of credentials obtained from a Short Lived Credentials Service. Default value is 1024. This attribute corresponds to the `-Z` command line option of `arcslcs`.

Example: `keysize=2048`

certificatelifetime

Sets lifetime (in hours, starting from current time) of user certificate which will be obtained from a Short Lived Credentials Service. This attribute corresponds to the `-L` command line option of `arcslcs`.

Example: `certificatelifetime=12`

slcs

Sets the URL to the Short Lived Certificate Service. This attribute corresponds to the `-S` command line option of `arcslcs`.

Example: `slcs=https://127.0.0.1:60000/slcs`

storedirectory

Sets directory which will be used to store credentials obtained from a Short Lived Credential Service. This attribute corresponds to the `-D` command line option of `arcslcs`.

Example: `storedirectory=/home/mycredentials`

jobdownloaddirectory

Sets directory which will be used as the default job download directory. This attribute corresponds to the `-D` command line option of `arcget`.

Example: `jobdownloaddirectory=/home/myjobs`

idpname

Sets Identity Provider name (Shibboleth) to which user belongs. It is used for contacting Short Lived Certificate Services. This attribute corresponds to the `-I` command line option of `arcslcs`.

Example: `idpname=https://idp.testshib.org/idp/shibboleth`

4.2 Service blocks

These blocks are only available in ARC 12.05!

Each service is configured through its own block. Each service has to have unique alias name, which is used to refer to this service. The services can be grouped into multiple groups. Then the name of the group can be used in the command line to select all members of the group. Possible names of blocks are [registry/<alias>] for registry services and [computing/<alias>] for computing services.

Example:

```
[registry/index1]
url = ldap://index2.nordugrid.org:2135/Mds-Vo-name=NorduGrid,o=grid

[registry/index2]
url = ldap://index2.nordugrid.org:2135/Mds-Vo-name=NorduGrid,o=grid
registryinterface = org.nordugrid.ldapeciis
default = yes
group = favs

[computing/myce]
url = myce.example.com

[computing/ce]
url = https://ce.example.com:60000/arex
infointerface = org.ogf.emies
submissioninterface = org.ogf.emies
default = yes
group = favs
```

url

The URL of the service. The URL can be shortened to the domain name, in which case the client will try to guess the missing parts (protocol, port, paths). This is the only **mandatory** option in a service block.

Example: url=https://example.com:60000/arex

default

Setting this to **yes** indicates that this service should be used by default by the commands if there were no computing elements or registries given as command line arguments.

Example: default=yes

group

The name of the group the service belongs to. Services can be selected by specifying the name of the group as command line arguments instead of the alias of the service. A service can belong to multiple groups.

Example:

```
group=favs
group=fast
```

infointerface

The interface of the service through which the computing element information should be retrieved Example:

```
infointerface=org.nordugrid.ldapng
```

Possible information interfaces are:

- org.nordugrid.ldapng
- org.nordugrid.ldapglue1
- org.nordugrid.ldapglue2
- org.nordugrid.wsrfglue2
- org.ogf.emies

submissioninterface

The interface of the service with which the jobs should be submitted.

Example:

```
submissioninterface=org.nordugrid.gridftpjob
```

Possible submission interfaces are:

- org.nordugrid.gridftpjob
- org.ogf.bes
- org.ogf.emies

registryinterface

The interface of the service with which the registry can be queried.

Example:

```
registryinterface=org.nordugrid.ldapeciis
```

Possible registry interfaces are:

- org.nordugrid.ldapeciis
- org.nordugrid.emir (*subject to change*)

4.3 srms.conf

If any data management commands are used with the Storage Resource Management (SRM) [8] protocol, the file

```
$HOME/.arc/srms.conf
```

(or its analogue on non-Linux platforms) may be created to store cached information on these services. For more information see the description inside this file.

4.4 Block [alias]

This block is deprecated in ARC 12.05!

Users often prefer to submit jobs to a specific site; since contact URLs (and especially end-point references) are very long, it is very convenient to replace them with aliases. Block [alias] simply contains a list of alias-value pairs.

Alias substitutions is performed in connection with the `-c` command line switch of the ARC clients.

Aliases can refer to a list of services (separated by a blank space).

Alias definitions can be recursive. Any alias defined in a list that is read before a given list can be used in alias definitions in that list. An alias defined in a list can also be used in alias definitions later in the same list.

Examples:

```
[alias]

arc0=computing:ARC0:ldap://ce.ng.org:2135/nordugrid-cluster-name=ce.ng.org,
Mds-Vo-name=local,o=grid
arc1=computing:ARC1:https://arex.ng.org:60000/arex
cream=computing:CREAM:ldap://cream.glite.org:2170/o=grid
crossbrokering=arc0 arc1 cream
```

4.5 Deprecated configuration files

ARC configuration file in releases 0.6 and 0.8 has the same name and the same format. Only one attribute is preserved (`timeout`); other attributes unknown to newer ARC versions are ignored.

In $\text{ARC} \leq 0.5.48$, configuration on Linux platforms was done via files `$HOME/.ngrc`, `$HOME/.nggiislist` and `$HOME/.ngalias`.

The main configuration file `$HOME/.ngrc` could contain user's default settings for the verbosity level, the information system query timeout and the download directory used by `ngget`. A sample file could be the following:

```
# Sample .ngrc file
# Comments starts with #
NGDEBUG=1
NGTIMEOUT=60
NGDOWNLOAD=/tmp
```

If the environment variables `NGDEBUG`, `NGTIMEOUT` or `NGDOWNLOAD` were defined, these took precedence over the values defined in this configuration. Any command line options override the defaults.

The file `$HOME/.nggiislist` was used to keep the list of default GIIS server URLs, one line per GIIS (see `giis` attribute description above).

The file `$HOME/.ngalias` was used to keep the list of site aliases, one line per alias (see `alias` attribute description above).

Acknowledgements

This work was supported in parts by: the Nordunet 2 program, the Nordic DataGrid Facility, the EU KnowARC project (Contract nr. 032691), the EU EMI project (Grant agreement nr. 261611) and the Swedish Research council via the eSENCE strategic research program.

Bibliography

- [1] gLite, Lightweight Middleware for Grid Computing. Web site. URL <http://glite.web.cern.ch/glite/>.
- [2] A. Anjomshoa et al. Job Submission Description Language (JSDL) Specification, Version 1.0 (first errata update). GFD-R.136, July 2008. URL <http://www.gridforum.org/documents/GFD.136.pdf>.
- [3] Ann L. Chervenak et al. Performance and Scalability of a Replica Location Service. In *Proceedings of the 13th IEEE International Symposium on High Performance Distributed Computing (HPDC'04)*, pages 182–191. IEEE Computer Society Press, 2004. ISBN 0-7803-2175-4.
- [4] M. Ellert, B. Mohn, I. Márton, and G. Rőcsei. *libarcclient – A Client Library for ARC*. The NorduGrid Collaboration. URL http://www.nordugrid.org/documents/client_technical.pdf. NORDUGRID-TECH-20.
- [5] I. Foster and C. Kesselman. Globus: A Metacomputing Infrastructure Toolkit. *International Journal of Supercomputer Applications*, 11(2):115–128, 1997. Available at: <http://www.globus.org>.
- [6] A. Konstantinov. *The ARC Computational Job Management Module – A-REX*. The NorduGrid Collaboration. URL <http://www.nordugrid.org/documents/a-rer.pdf>. NORDUGRID-TECH-14.
- [7] F. Pacini and A. Maraschini. *Job Description Language attributes specification*, 2007. URL <https://edms.cern.ch/document/590869/1>. EGEE-JRA1-TEC-590869-JDL-Attributes-v0-8.
- [8] A. Sim, A. Shoshani, et al. The Storage Resource Manager Interface (SRM) Specification v2.2. GFD-R-P.129, May 2008. URL <http://www.ggf.org/documents/GFD.129.pdf>.
- [9] O. Smirnova. *Extended Resource Specification Language*. The NorduGrid Collaboration. URL <http://www.nordugrid.org/documents/xrsl.pdf>. NORDUGRID-MANUAL-4.
- [10] M. Smith and T. A. Howes. *LDAP : Programming Directory-Enabled Applications with Lightweight Directory Access Protocol*. Macmillan, 1997.

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the definition; numbers in roman refer to the pages where the entry is used.

A		arcmkdir	30	arcsync	18
arccat	15	arcproxy	7	arctest	31
arcclean	21	arcnew	22	B	
arccp	28	arcresub	24	broker	13
arcget	16	arcresume	23	C	
arcinfo	19	arcrm	29	commands	
arckill	19	arcslcs	9	arccat	15
arcls	27	arcsrmping	30	arcclean	21
arcmigrate	26	arcsb	9		

arccp	28	cacertificatesdirectory	41	storedirectory	42
arcget	16	certificatelifetime	42	submissioninterface	39, 44
arcinfo	19	certificatepath	40	timeout	39
arckill	19	default	43	url	43
arcls	27	defaultservices	38	username	41
arcmigrate	26	deprecated files	45	verbosity	39
arcmkdir	30	group	43	vomsserverpath	41
arcproxy	7	idpname	42		
arcnew	22	infointerface	39, 44	D	
arcresub	24	jobdownloaddirectory	42	data management	27
arcresume	23	joblist	40		
arcrm	29	keypassword	41	J	
arcls	9	keypath	40	job ID	11
arcsrmping	30	keysize	41	job management	9
arcsub	9	password	41		
arcsync	18	proxypath	40	S	
arctest	31	registryinterface	44	security	7
configuration		rejectdiscovery	38	submit job	9
bartender	40	rejectmanagement	38		
brokerarguments	39	rejectservices	38	U	
brokername	39	slcs	42	URL	33
cacertificatepath	41	srms.conf	44	options	34
				URLs	33